

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Package

Weight Per each

HBLDS100 NM Sloped Disc, 100A Unfused, 4X *Hubbell Wiring Devices*

| Hubbell Wiring Devices | |
|------------------------------------|---|
| Catalog Number | HBLDS100 |
| Manufacturer | Hubbell Wiring Devices |
| Description | Industrial Grade, Motor Disconnect Switch, Unfused, 3 Pole, 100A 600V Ac, Screw Terminals, IP69K, Nema Type 4X, 12 Non-Metallic Sloped Top Enclosure, Culus, NSF, Ce, UI 508 / UI 60947-4-1a |
| Weight per unit | 6.1 (lbs/each) |
| Product Category | 20240715144702 |
| Features | |
| operating cycles | 10,000 |
| Descriptions | |
| Description | NM SLOPED DISC, 100A UNFUSED, 4X |
| extra long description | HWDK HBLDS100 NM SLOPED DISC, 100A |
| Features | NEC section 430.102(B) requires each motor controller to have a disconnect within line of sight from the motor and driven equipment. Hubbell's Circuit-Lock® Unfused Disconnect Switches are UL listed as a manual motor controller and also "suitable as a motor disconnect" and meet these code requirements. |
| Long Description | Industrial Grade, Motor Disconnect Switch, Unfused, 3 Pole, 100A 600V AC, Screw Terminals, IP69k, NEMA Type 4X, 12 Non-Metallic Sloped Top Enclosure, cULus, NSF, CE, UL 508 / UL 60947-4-1A |
| Product Type | NM Sloped Disc, 100A Unfused, 4X |
| Manufacturer Information | |
| Brand | WIRING DEVICE-KELLEMS |
| GTIN | 00783585763330 |
| Manufacturers Part Number | HBLDS100 |
| series | Non-Fused |
| UPC | 783585763330 |
| Taxonomies, Classifications, and G | Categories |
| Category Description | Fuses & Fuse Accessories |
| Туре | Disconnect Switches |
| Packaging | |
| Carton | 1 |
| Dealers | |

0 6.07

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

| Application | Heavy Duty Industrial and/or Washdown |
|--------------------------|---------------------------------------|
| Enclosure | IP69k and UL Type 4X, 12 |
| environmental conditions | Indoor and Outdoor |
| standard | cULus Listed |