

## Stainless Steel Circuit-Lock® Unfused Switched Disconnect Enclosures\*

Description	30 Amp	60 Amp	100 Amp
Square Top disconnect switch.	<b>HBLDS3SS</b>	<b>HBLDS6SS</b>	<b>HBLDS10SS</b>
Square Top disconnect switch with HBLAC1 auxiliary contact.	<b>HBLDS3SSAC</b>	<b>HBLDS6SSAC</b>	<b>HBLDS10SSAC</b>
Square Top disconnect switch for use with variable frequency drives.	<b>HBLDS3SSVFD</b>	<b>HBLDS6SSVFD</b>	<b>HBLDS10SSVFD</b>
Sloped Top disconnect switch.	<b>HBLDS3SSR</b>	<b>HBLDS6SSR</b>	<b>HBLDS10SSR</b>
Sloped Top disconnect switch with HBLAC1 auxiliary contact.	<b>HBLDS3SSRAC</b>	<b>HBLDS6SSRAC</b>	<b>HBLDS10SSRAC</b>
Sloped Top disconnect switch for use with variable frequency drives.	<b>HBLDS3SSRVFD</b>	<b>HBLDS6SSRVFD</b>	<b>HBLDS10SSRVFD</b>
Sloped Top disconnect, Pre-drilled 4X with (2) 3/4 inch stainless steel hubs.	<b>HBLDS3SSR2K</b>	—	—
Sloped Top enclosure, Blank.	<b>HBLDSSRNK3</b>	<b>HBLDSSRNK6</b>	—



**HBLDS3SS**



**HBLDS3SSJ**

## Stainless Steel Disconnects with LEDs

Description	Stainless Steel Square Top	Stainless Steel Sloped Top
Disconnect switch with LEDs.	<b>HBLDS3SSP</b>	<b>HBLDS3SSRP</b>
Disconnect with Jog switch and LEDs.	—	<b>HBLDS3SSRPJ</b>

Note: For use with 3Ø Y configurations only.

## Stainless Steel Disconnects with Jog Switch

Description	Stainless Steel Square Top	Stainless Steel Sloped Top
30A disconnect with Jog switch.	<b>HBLDS3SSJ</b>	<b>HBLDS3SSRJ</b>



**HBLDS3SSR**

## Stainless Steel Conduit Hubs

Description	Catalog Number
3/4 inch stainless steel conduit hub.	<b>HUB75SS</b>
1 1/4 inch stainless steel conduit hub.	<b>HUB125SS</b>



**HBLDS3SSRPJ**

## Auxiliary Contacts for 30, 60 and 100 Amp Switch, NEMA A600 Pilot Duty

Description	Catalog Number
"Break After Main Break", 1 set of n/o contacts, 1 set of n/c contacts.	<b>HBLAC1**</b>
"Break Before Main Break", 1 set of n/o contacts for use with variable frequency drives.	<b>HBLAC2**</b>

Note: \*Certified by NSF, International.

\*\*Up to two auxiliary contacts per enclosure. Not for use with HBLDS33ACNK.

30A Units are supplied with one 3/4 in. NPT Raintight conduit fitting.

60A and 100A Units are supplied with two 1 1/4 in. NPT Raintight conduit fittings.

