

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Type

HFD3225 HFD 3P 600VAC Rated Load Terms Only *Eaton Corp*

Catalog Number	HFD3225
Manufacturer	Eaton Corp
Description	Eaton Series C Complete Molded Case Circuit Breaker, F-Frame, HFD, Complete Breaker, Fixed Thermal, Fixed Magnetic Trip Type Three-Pole, 225 A, 600 Vac, 250 VDC, Load Side, 50/60 HZ
Weight per unit	5.0 (lbs/each)
Product Category	3 Pole
eatures	
Current Rating	225 A
dimensions	3.3800 IN X 4.1300 IN X 4.1300 IN
frame	F
media	Yes
Poles	3
Voltage Rating	600 VAC, 250 VDC
Descriptions	
Description	HFD 3P 600VAC RATED LOAD TERMS ONLY
extra long description	ETN HFD3225 HFD 3P 600VAC RATED LOA
Features	Experience the superior quality of the Eaton Series C Molded Case Circuit Breaker. The Series C circuit breaker is ideal for panelboards, switchboards, motor control centers, and busway applications. Choose from a premier selection of trip units including thermal magnetic, electronic, and magnetic only switches. Available for systems up to 600 VAC or 250 VDC with current ratings up to 800A.
Long Description	Eaton Series C complete molded case circuit breaker, F-frame, HFD, Complete breaker, Fixed thermal, Fixed magnetic trip type, Three-pole, 225 A, 600 Vac, 250 Vdc, Load side, 50/60 Hz
Product Type	LIED 2D (00)/AC Datad Load Torres Only
Nanufacturer Information	
Brand	Eaton
GTIN	00786679015421
Mari Carl III David Ni III III	HFD3225
UPC	786679015421
Taxonomies, Classifications, and C Category Description	Categories MOLDED CASE BREAKERS
_	

Molded case circuit breaker



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	
Weight Per each	5
Uses, Certifications, and Standards	
Application	Elec Assemblies, Panels & EOEM - Electrical Assemblies, Panels
	and EOEMs
standard	UL Listed