

High-Lumen Flood LED Luminaires

The Solution You Need

The HLF high-lumen floodlights from Lithonia Lighting are the ideal LED solution for replacing 400W and 1000W metal halide floodlights by delivering what you need – a no-compromise solution that saves energy and lowers maintenance costs.

A No-Compromise Solution

With up to 64,000 lumens, the HLF high-lumen floodlight produces enough light to replace up to 1000W metal halide floodlights with ease. Combine this power with easy mounting options, such as our universal slipfitter or yoke mounts, and you can retrofit virtually any existing 1000W HID floodlight installation.

Energy Savings

The HLF provides typical energy savings of 54% when replacing 1000W metal halide without sacrificing light levels. Combine this with Acuity Controls ROAM® for site-wide dimming and monitoring—and the energy savings are even greater.

Lower Maintenance Costs

With a life expectancy of over 20 years, the HLF is designed to save money. Eliminating up to ten expensive metal halide lamp changes over the life of the product, maintenance costs are virtually eliminated. This is especially important at hard-to-reach mounting heights where lamp-replacement costs are inconvenient and expensive.



Quick Facts:

12

- Replaces 400W and 1000W metal halide floodlights
- Lumen packages ranging from 19,000 to 64,000
- Eight optics designed to meet unique application requirements, including a 7° optic
- Universal yoke and integral slip fitter mounting options for easy 1-for-1 retrofit
- Instant-on, avoiding long restrike times of traditional HID sources

AcuityBrands.



Outdoor

Ordering Information

EXAMPLE: HLF2 LED P1 40K WFL MVOLT IS DDBXD

HLF1	& HLF2	

Ρ3

32,638

295W

111

64,248

Series	Package	Color te	empera	ature	Distrib	ution	Voltage	Mounting		Options		Finish		
HLF1 LED HLF2 LED	P1 P2 P3	30K 40K 50K	3000 4000 5000) K	VNSP NSP SP NFL MNFL WFL	Very Narrow Spot Narrow Spot Spot Narrow Flood Medium Flood Wide Flood	MVOLT 120 208 240 277 347 480	Shipped i IS YKC62	Integra 2-3/8″	l slipfitter (fits D.D. tenon) th 16-3	Shipped PER5 SF DF CFB Shipped UBV FV VG WG	installed NEMA twist-lock receptacle only (no controls) Single fuse (120, 277, 347V) Double fuse (208, 240, 480V) Black faceplate separately Upper/bottom visor accessory Full Baffle accessory Vandal guard accessory Wire guard accessory	DDBXD DBLXD DNAXD DWHXD	Dark bronze Black Natural aluminum White
	HLF1 (4000K, MFL)				HLF2 (4000K, M			*Consult p	roduct spec sheet for more details					
Performanc	e Package	Lume	ens	Input	Watts	LPW	Lumens	Input W	atts	LPW				
P1	1	19,3	70	166	δW	117	39,250	328V	V	120				
P2	2	27,3	54	246	5W	111	53,847	487V	V	111				

Optic Options
Image: Construction of the second secon

598W

107

LED Floodlighting Solutions

D-Series Floods

50W - 400W Metal Halide Replacement

HLF High-Lumen Floods

400W - 1000W Metal Halide Replacement

		A	1255		
MODEL #	DSXF1	DSXF2	DSXF3	HLF1	HLF2
Lumens	3,977	7,670	18,992	32,638	64,248
Metal Halide Replacement	50W - 150W	150W - 250W	250W - 400W	400W+	1000W+
Input Watts	37W	74W	183W	295W	598W
LPW	107	104	104	111	107
DesignLights Consortium® qualified product	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark

Learn more about our LED floodlighting solutions at www.lithonia.com





High-Lumen Flood LED Luminaires

The Solution You Need

The HLF high-lumen floodlights from Lithonia Lighting are the ideal LED solution for replacing 400W and 1000W metal halide floodlights by delivering what you need – a no-compromise solution that saves energy and lowers maintenance costs.

A No-Compromise Solution

With up to 64,000 lumens, the HLF high-lumen floodlight produces enough light to replace up to 1000W metal halide floodlights with ease. Combine this power with easy mounting options, such as our universal slipfitter or yoke mounts, and you can retrofit virtually any existing 1000W HID floodlight installation.

Energy Savings

The HLF provides typical energy savings of 54% when replacing 1000W metal halide without sacrificing light levels. Combine this with Acuity Controls ROAM® for site-wide dimming and monitoring—and the energy savings are even greater.

Lower Maintenance Costs

With a life expectancy of over 20 years, the HLF is designed to save money. Eliminating up to ten expensive metal halide lamp changes over the life of the product, maintenance costs are virtually eliminated. This is especially important at hard-to-reach mounting heights where lamp-replacement costs are inconvenient and expensive.



Quick Facts:

12

- Replaces 400W and 1000W metal halide floodlights
- Lumen packages ranging from 19,000 to 64,000
- Eight optics designed to meet unique application requirements, including a 7° optic
- Universal yoke and integral slip fitter mounting options for easy 1-for-1 retrofit
- Instant-on, avoiding long restrike times of traditional HID sources

AcuityBrands.



Outdoor

Ordering Information

EXAMPLE: HLF2 LED P1 40K WFL MVOLT IS DDBXD

HLF1	& HLF2	

Ρ3

32,638

295W

111

64,248

Series	Package	Color te	empera	ature	Distrib	ution	Voltage	Mounting		Options		Finish		
HLF1 LED HLF2 LED	P1 P2 P3	30K 40K 50K	3000 4000 5000) K	VNSP NSP SP NFL MNFL WFL	Very Narrow Spot Narrow Spot Spot Narrow Flood Medium Flood Wide Flood	MVOLT 120 208 240 277 347 480	Shipped i IS YKC62	Integra 2-3/8″	l slipfitter (fits D.D. tenon) th 16-3	Shipped PER5 SF DF CFB Shipped UBV FV VG WG	installed NEMA twist-lock receptacle only (no controls) Single fuse (120, 277, 347V) Double fuse (208, 240, 480V) Black faceplate separately Upper/bottom visor accessory Full Baffle accessory Vandal guard accessory Wire guard accessory	DDBXD DBLXD DNAXD DWHXD	Dark bronze Black Natural aluminum White
	HLF1 (4000K, MFL)				HLF2 (4000K, M			*Consult p	roduct spec sheet for more details					
Performanc	e Package	Lume	ens	Input	Watts	LPW	Lumens	Input W	atts	LPW				
P1	1	19,3	70	166	δW	117	39,250	328V	V	120				
P2	2	27,3	54	246	5W	111	53,847	487V	V	111				

Optic Options
Image: Construction of the second secon

598W

107

LED Floodlighting Solutions

D-Series Floods

50W - 400W Metal Halide Replacement

HLF High-Lumen Floods

400W - 1000W Metal Halide Replacement

		A	1255		
MODEL #	DSXF1	DSXF2	DSXF3	HLF1	HLF2
Lumens	3,977	7,670	18,992	32,638	64,248
Metal Halide Replacement	50W - 150W	150W - 250W	250W - 400W	400W+	1000W+
Input Watts	37W	74W	183W	295W	598W
LPW	107	104	104	111	107
DesignLights Consortium® qualified product	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark

Learn more about our LED floodlighting solutions at www.lithonia.com

