



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

13405 Stemmons Frwy
75234-0000, TX Farmers Branch
Phone: 972-206-0016
Fax: 972-352-2818



HSTT1248Q Heatshrink Tubing BLK 1/8

Panduit Corporation

| | |
|------------------|--|
| Catalog Number | HSTT1248Q |
| Manufacturer | Panduit Corporation |
| Description | Panduit Thin-Wall Heat Shrink Tubing Shrinks Around Wires, Connectors, Joints and Terminals When Heated to Protect Against Abrasion, Fire and Chemicals. Cross-Link Polyolefin, 0.12"D X 3.94'L (3.2MM X 1.2M), Black, 25PC. |
| Weight per unit | 0.7600 (lbs/each) |
| Product Category | Insulating Materials |

Features

| | |
|------------------|-----------------|
| flammability | Flame Retardant |
| media | Yes |
| outside diameter | 0.12 |
| Shrink Ratio | 2:1 |

Material, Color, and Finish

| | |
|-------|-------|
| Color | Black |
|-------|-------|

Dimensions and Weight

| | |
|-----------|------|
| Thickness | 0.02 |
|-----------|------|

Descriptions

| | |
|------------------------|--|
| Description | HEATSHRINK TUBING BLK 1/8 |
| extra long description | PAN HSTT12-48-Q Dry-Shrink HSTT12-4 |
| Long Description | Panduit Thin-wall Heat Shrink Tubing shrinks around wires, connectors, joints and terminals when heated to protect against abrasion, fire and chemicals. Cross-link Polyolefin, 0.12"D x 3.94'L (3.2mm x 1.2m), Black, 25pc. |
| Product Type | Dry-Shrink HSTT12-48-Q Heatshrink, Black, Po, 0.125" to 0.06 |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | PANDUIT |
| GTIN | 00074983905898 |
| Manufacturers Part Number | HSTT12-48-Q |
| UPC | 074983905898 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|------------------|
| Category Description | HEAT/COLD SHRINK |
| Type | Heat-Shrink |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

13405 Stemmons Frwy
75234-0000, TX Farmers Branch
Phone: 972-206-0016
Fax: 972-352-2818

Packaging

Carton 25

Weight Per each 0.76

Uses, Certifications, and Standards

Application For Dry Locations

standard UL Recognized