



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## HSTT1948Q Heatshrnk Tubing 3/16 BLK

*Panduit Corporation*

|                  |   |
|------------------|---|
| Catalog Number   | HSTT1948Q   |
| Manufacturer     | Panduit Corporation   |
| Description      | The HSTT19-48-Q Thin Wall Heat Shrink Tubing Shrinks Around Wires, Connectors, Joints, and Terminals When Heated to Protect Against Abrasion. Applications Include Insulating and Protecting Wires/Cables In Indoor, Dry Locations. Shrink Ratio: 2:1. Temperature Range: -67°F to 275°F (-55°C to 135°C). Flame Retardant, Cross-Linked Polyolefin. 0.187" Diameter X 4' Long (4.8 MM X 1.2 M). Color Black. 25 Per Package. |
| Weight per unit  | 0.8350 (lbs/each)   |
| Product Category | Insulating Materials  |

### Features

|                  |                 |
|------------------|-----------------|
| flammability     | Flame Retardant |
| media            | Yes             |
| outside diameter | 0.19            |
| Shrink Ratio     | 2:1             |

### Material, Color, and Finish

|       |       |
|-------|-------|
| Color | Black |
|-------|-------|

### Dimensions and Weight

|           |      |
|-----------|------|
| Thickness | 0.02 |
|-----------|------|

### Descriptions

|                        |   |
|------------------------|---|
| Description            | HEATSHRNK TUBING 3/16 BLK   |
| extra long description | PAN HSTT19-48-Q Dry-Shrink™ HSTT19-   |
| Long Description       | The HSTT19-48-Q Thin Wall Heat Shrink Tubing shrinks around wires, connectors, joints, and terminals when heated to protect against abrasion. Applications include insulating and protecting wires/cables in indoor, dry locations. Shrink ratio: 2:1. Temperature range: -67°F to 275°F (-55°C to 135°C). Flame retardant, cross-linked polyolefin. 0.187" Diameter x 4' Long (4.8 mm x 1.2 m). Color Black. 25 per package. |
| Product Type           | Dry-Shrink™ HSTT19-48-Q Heatshrink, Black, Po, 4' L, 0.187"   |

### Manufacturer Information

|                           |                |
|---------------------------|----------------|
| Brand                     | PANDUIT        |
| GTIN                      | 00074983905904 |
| Manufacturers Part Number | HSTT19-48-Q    |
| UPC                       | 074983905904   |



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Category Description.....HEAT/COLD SHRINK

Type.....Heat-Shrink

## Packaging

Carton.....25

Weight Per each.....0.835

## Uses, Certifications, and Standards

Application.....For Dry Locations;Insulating and protecting wires and cables

standard.....Mil Spec: AMS-DTL-23053/5 Class 1;UL: E122770