



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## HSTT2548QC HT Shrink Tubing

*Panduit Corporation*

|                  |  |
|------------------|--|
| Catalog Number   | HSTT2548QC   |
| Manufacturer     | Panduit Corporation  |
| Description      | The HSTT25-48-QC Thin Wall Heat Shrink Tubing Shrinks Around Wires, Connectors, Joints, and Terminals When Heated to Protect Against Abrasion. Applications Include Insulating and Protecting Wires/Cables In Indoor, Dry Locations. Shrink Ratio: 2:1. Temperature Range: -67°F to 275°F (-55°C to 135°C). Cross-Linked Polyolefin. 0.25" Diameter X 4' Long (6.4 MM X 1.2 M). Color Clear. 25 Per Package. |
| Weight per unit  | 1.1 (lbs/each)   |
| Product Category | Insulating Materials   |

### Features

|                                 |       |
|---------------------------------|-------|
| continuous operating temperatur | 275   |
| flammability                    | N/A   |
| Inside Diameter                 | 0.125 |
| media                           | Yes   |
| outside diameter                | 0.25  |
| Shrink Ratio                    | 2:1   |

### Material, Color, and Finish

|       |       |
|-------|-------|
| Color | Clear |
|-------|-------|

### Dimensions and Weight

|           |       |
|-----------|-------|
| Thickness | 0.025 |
|-----------|-------|

### Descriptions

|                        |  |
|------------------------|--|
| Description            | HT SHRINK TUBING   |
| extra long description | PAN HSTT25-48-QC Dry-Shrink™ HSTT25  |
| Long Description       | The HSTT25-48-QC Thin Wall Heat Shrink Tubing shrinks around wires, connectors, joints, and terminals when heated to protect against abrasion. Applications include insulating and protecting wires/cables in indoor, dry locations. Shrink ratio: 2:1. Temperature range: -67°F to 275°F (-55°C to 135°C). Cross-linked polyolefin. 0.25" Diameter x 4' Long (6.4 mm x 1.2 m). Color Clear. 25 per package. |
| Product Type           | Dry-Shrink™ HSTT25-48-QC Heatshrink, Clear, Po, 4' L, 0.25"  |



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Manufacturer Information

|                           |                |
|---------------------------|----------------|
| Brand                     | PANDUIT        |
| GTIN                      | 00074983906628 |
| Manufacturers Part Number | HSTT25-48-QC   |
| UPC                       | 074983906628   |

## Taxonomies, Classifications, and Categories

|                      |                    |
|----------------------|--------------------|
| Category Description | HEAT/COLD SHRINK   |
| Type                 | Heat Shrink Tubing |

## Packaging

|                 |      |
|-----------------|------|
| Carton          | 25   |
| Weight Per each | 1.09 |

## Uses, Certifications, and Standards

|             |   |
|-------------|---|
| Application | For Dry Locations; Insulating and protecting wires and cables |
| standard    | Mil Spec: AMS-DTL-23053/5 Class 2                             |