

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

ITCSN1100 Heat Shrink Heavy-Wall Cable Sleeve Itcsn-1100 Minnesota Mining (3M)

Catalog Number	ITCSN1100
Manufacturer	Minnesota Mining (3M)
Description	3M™ Heat Shrink Cable Sleeve Itcsn Is A Heavy Wall Sleeve That Provides Abrasion, Corrosion and Chemical Resistance. This Sleeve Has A 3:1 Shrink Ratio to Offer Electrical Insulation For 1 KV Rated Applications. It Features A Cross Linked Polyolefin Construction That Provides Moisture Seal Protection.
Weight per unit	0.1669 (lbs/each)
Product Category	Splicing & Terminating Kits
Descriptions	
Description	HEAT SHRINK HEAVY-WALL CABLE SLEEVE ITCSN-1100
extra long description	3M 7010305769 3M™ Heat Shrink Heavy
Features	3M™ Heat Shrink Cable Sleeve ITCSN is a split resistant sleeve with a factory applied adhesive/sealant that offers reliable performance for electrical splices, connections and terminations It is perfect for insulating secondary splices, direct buried, submersible or dig in repairs, as well as physical protection of high voltage, air insulated connectors or lugs. It withstands temperatures of 67 to 230 degrees F (55 to 110 degrees C). UL Listed, CSA Certified and RoHS 2011/65/EU Compliant.
Long Description	3M™ Heat Shrink Cable Sleeve ITCSN is a heavy wall sleeve that provides abrasion, corrosion and chemical resistance. This sleev has a 3:1 shrink ratio to offer electrical insulation for 1 kV rated applications. It features a cross linked polyolefin construction that provides moisture seal protection.
Product Type	3M™ Heat Shrink Heavy-Wall Cable Sleeves Itcsn
/lanufacturer Information	
Brand	3M
GTIN	00051128600795
Manufacturers Part Number	IT1.100BK9"P
UPC	051128600795
axonomies, Classifications, and (Categories
Category Description	HEAT/COLD SHRINK
Туре	Heavy Wall
Packaging	
Carton	12

0.1669

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards		
standard	UL, CSA	