

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

K2A40U 300-800 2 Conductor Al/Cu Lug Burndy LLC

Catalog Number	K2A40U
Manufacturer	Burndy LLC
Description	Aluminum Universal Terminal, 2 Conductor, 1 Hole, 300-800 Kcmil, 5/8" Stud, 2 Screws, Al/Cu Rated, Tin Plated.
Weight per unit	0.9500 (lbs/each)
Product Category	Large Terminals & Connectors
Features	
Material	Aluminum
Number of Conductors	2
pallet quantity	30
Descriptions	
Description	300-800 2 CONDUCTOR AL/CU LUG
extra long description	BUR K2A40U TWO:300-800 DUAL RATED
Long Description	Aluminum Universal Terminal, 2 Conductor, 1 Hole, 300-800 kcmil, 5/8" Stud, 2 Screws, Al/Cu Rated, Tin Plated.
Product Type	Terminal
Special Features	Features: These Dual-Rated Two-Conductor Lugs Are Constructed From High Strength Aluminum Alloy And Electro Tin-Plated To Provide Low Contact Resistance, Stud/bolt Hole Size: 5/8 IN, Number Of Screws: 1, Dimension T: 0.5 IN, Dimension D: 1.66 IN, Dimension N: 0.88 IN, Installation Torque: 550 IN-LB, Set Screw Type: Allen Key, Length: 3.38 IN, Width: 3.19 IN, Height: 1.94 IN
Manufacturer Information	
Brand	BURNDY
GTIN	00781810600252
Manufacturers Part Number	K2A40U
UPC	781810600252
Taxonomies, Classifications, and (-
	Comp & Mech Lugs and Butt Splices
Туре	Bolted Lugs & Terminals
Packaging	
Carton	
Package	3

0.95

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	For Aluminum And Copper Conductors
standard	UL 486A-486B
Temperature Rating	194