



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## KL471 A:2/0, B:2/0 Alu Comp Splice

*Abb Installation Products, Inc*

|                  |  |
|------------------|--|
| Catalog Number   | KL471  |
| Manufacturer     | Abb Installation Products, Inc   |
| Description      | Compression Splice, 2/0 Awg (Ascr);2/0 Awg (Stranded);3/0 Awg (Compact Conductor-Stranded) Conductor Size, Non-Insulated, Aluminum/Copper Conductor Material, Gray (Code) Insulation Color, 2 Conductors, 3.5 In Overall Length, Compression/Crimp Terminal, 600 V, 0.18 LB/Ea |
| Weight per unit  | 0.1820 (lbs/each)  |
| Product Category | Large Terminals & Connectors   |

### Features

|                      |             |
|----------------------|-------------|
| connection           | Compression |
| insulation           | None        |
| Material             | Aluminum    |
| Number of Conductors | 2           |

### Dimensions and Weight

|      |            |
|------|------------|
| Size | 3-1/2 Inch |
|------|------------|

### Descriptions

|                        |                                     |
|------------------------|-------------------------------------|
| Description            | A:2/0,B:2/0 ALU COMP SPLICE         |
| extra long description | ABB KL47-1 AL SERVENTR SPLICE A:2/0 |

### Manufacturer Information

|       |                      |
|-------|----------------------|
| Brand | Blackburn Mechanical |
| GTIN  | 00783786050390       |
| UPC   | 783786050390         |

### Taxonomies, Classifications, and Categories

|                      |                                     |
|----------------------|-------------------------------------|
| Category Description | Comp & Mech Lugs and Butt Splices   |
| Type                 | Compression Splice Service Entrance |

### Packaging

|                 |       |
|-----------------|-------|
| Carton          | 25    |
| Package         | 250   |
| Weight Per each | 0.182 |

### Uses, Certifications, and Standards

|                          |  |
|--------------------------|--|
| Application              | For Combinations of Aluminum-to-Aluminum and Aluminum-to-Copper Conductors |
| environmental conditions | All Seasons / Conditions   |
| Mounting                 | None   |
| standard                 | Passes the requirements of ANSI C119.4                                     |