	MSD	SR	epo	rto	
Prepared For:	Klein Tools	, Inc.			
Address:	450 Bond S	Street Lincolr	shire, IL, 60	069 USA	
Product Name:	Power Ban	k			
Model:	KTB1				
Nominal Voltage:	Input: 5V Output: 5V	/9V/12V			
Rated Capacity:	10050mAh	, 36.48Wh			
Weight:	230.5g		S		S
Dimension:	106.5mm×6	67.6mm×28.	0mm (L×W×	T)	
Prepared By:	1B/F., Build	TCT Testing ding 1, Yibao rict, Shenzho	olai Industria	I Park, Qia	otou, Fuyong
Report No.:	TCT180815	5M004			
(C)					
Vritten by: <u>Sum</u>	imer Yang	Appro	ved by:	Allen &	m (G)
	America Zara			ASSTING 7	
nspected by:	my kng	_	Date:	2017.0	

1

Г

This report shall not be reproduced except in full, without the written approval of Shenzhen TCT Testing Technology Co., Ltd.

Material Safety Data Sheet

Material Safety Data Sheet Section 1- Chemical Product & Company Identification Product Name: Power Bank Manufacture: Dongguan DBK Energy Technology Co., Ltd No.51 Zhangshen Middle Road, Xuzhen Community, Zhangmutou Address: Town, Dongguan, Guangdong, P.R. China Contact Person: Jacken GUO Tel: +86-755-61861886 Fax: +86-755-61861886 Emergency Tel: +86-755-61861886 E-mail: 1-rd019@dbkbattery.com Item Code: TCT180815M004 Section 2- Hazards Identification Classification of See section 14. Danger Primary Route(s) Eye, skin contact, ingestion. of Exposure The batteries are not hazardous when used according to the instructions of manufacturer under normal conditions. In case of abuse, there's Hazard of rupture, fire, heat, leakage of internal components, which could cause casualty loss. Abuses Health Hazard including but not limited to the following cases: charged for long time, short circuited, put into fire, whacked with hard object, punctured with acute object, crushed, and broken. Report No.: TCT180815M004 Page 2 of 8 Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

Material Safety Data Sheet

Section 3- Composition/Information on Ingredients

Li-ion Battery (Contained In Power Bank) is a mixture.

Chemical Name	Concentration or concentration ranges (%)	CAS Number
Lithium Cobalt Oxide (CoLiO ₂)	30-60	12190-79-3
Graphite	10-30	7782-42-5
Phosphate(1-), hexafluoro-, lithium	10-30	21324-40-3
Copper	5-10	7440-50-8
Aluminum foil	1-5	7429-90-5
Nickel	1-5	7440-02-0
PVC (Chloroethylene, polymer)	1-5	9002-86-2

Labeling according to EC directives.

No symbol and Hazard phrase are required.

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

Section 4- First Aid Measures

Eye	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.
Skin	Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.
Inhalation	Remove from exposure and move to fresh air immediately. Use oxygen if available.
Ingestion	Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious. Call a physician.

Section 5- Fire Fighting Measures

Characteristics of Hazard	Dusts at sufficient co generates toxic fume	m explosive mixtures with air. Combustic	on
Hazardous Combustion Products	Carbon dioxide.		Contraction of the second seco

Report No.: TCT180815M004

eport No.: TCT180815M004	4		Page 3 of 8
Hotline: 400-6611-140	Tel: 86-755-27673339	Fax: 86-755-27673332	http://www.tct-lab.com

Fire-extinguishing Methods and Extinguishing Media	For small fires, use water	Material Safety Data Sheet
Attention in Fire-extinguishing	Wear self-contained breat (approved or equivalent) a	hing apparatus in pressure-demand, MSHA/NIOSH and full protective gear.
	No.	
Section 6- Accide	ental Release Meas	ures
Personal Precautio equipment, and em	ns, protective ergency procedures	In case of rupture. Attention! Corrosive material. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Refer to protective measures listed in Sections 7 and 8.
Environmental Pred	cautions	Prevent product from contaminating soil and from entering sewers or waterways.
Methods and mater	ials for Containment	Stop the leak if safe to do so. Contain the spilled liqui with dry sand or earth. Clean up spills immediately.
Methods and mater	ials for cleaning up	Absorb spilled material with an inert absorbent (dry sand or earth). Scoop contaminated absorbent into a acceptable waste container. Collect all contaminated absorbent and dispose of according to directions in Section 13. Scrub the area with detergent and water; collect all contaminated wash water for proper disposal.
Continue 7 Hand		
Section 7- Hand	ling and Storage	The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.
Storage	Ì	Store in a cool, dry, well-ventilated area away from incompatible substances. Store locked up. Keep out of the reach of children.
Other Precautions		In case of rupture. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Use personal protection equipment.

Section 8 - Exposure Controls/Persona	I Protection
Engineering Controls	Use adequate ventilation to keep airborne concentrations low. If used under conditions that generate particulates, the ACGIH TLV-TWA of 3mg/m ³ respirable fraction (10mg/m ³ total) should be observed.
	Eye and Face Protection: None required for consumer use. If there is a Hazard of contact: Tight sealing safety goggles. Face protection shield.
Personal Protective Equipment	Skin and Body Protection: None required for consumer use. If there is a Hazard of contact: Wear protective gloves and protective clothing.
	Respiratory Protection: No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Section 9- Physical and Chemical Properties

	Appearance: Prismatic	
Physical State	Color: Black	
(c)	Odour: If leaking, smells of medical ether.	$\langle \mathcal{C} \rangle$

Change in condition

TCT通测检测 TESTING CENTRE TECHNOLOGY

рН	Not applicable as supplied.
Flash Point	Not applicable unless individual components exposed.
Flammability	Not applicable unless individual components exposed.
Relative density:	Not applicable unless individual components exposed.
Solubility (water)	Not applicable unless individual components exposed.
Solubility (other)	Not applicable unless individual components exposed.

Section 10 – Stability and Reactivity	
Chemical Stability	Stable under recommended storage conditions.
Possibility of Hazardous Reactions	None under normal processing.
Conditions to Avoid	Exposure to air or moisture over prolonged periods.
Report No.: TCT180815M004 Hotline: 400-6611-140 Tel: 86-755-27673339	Page 5 of 8 Fax: 86-755-27673332 http://www.tct-lab.com

Incompatible materials		Acids, Oxidizing ag	ents, Bases.	
Hazardous Decomposition	Products	Carbon oxides.	Ś	
Section 11 – Toxicologic	al Information	٦		
Irritation			osure to internal contents irritating to the eyes and	•
Sensitization	(,	Not Available.	$\left(\mathcal{C}^{\prime}\right)$	
Reproductive Toxicity		Not Available.		
Toxicologically Synergistic I	Materials	Not Available.		
			C	
Section 12-Ecological Ir	nformation			
General note:	Ļ		ited product or large qua ater, water course or sev	
Anticipated behavior of a ch in environment/possible env impact/ ecotoxicity		Not Available.		
Section 13 – Disposal C	onsiderations	3		
Waste Treatment			e of in accordance with & local regulations.	
Attention for Waste Treatme	ent	trash. Shouldn't be temperature. Shou	shouldn't be treated as thrown into fire or place ldn't be dissected, pierce similarly. Best disposal	d in hig ed,
		(⁶)		
Section 14 – Transport	nformation			
UN number	3480			
Proper shipping name	Lithium ion bat	teries (limited to a max	imum of 30% SoC)	/
	9			

	Material Safety Data Shee	τ
Label(s) / Placard Required	Miscellaneous Lithium batt	
	a user needs to be aware of, or needs to comply with, in r conveyance either within or outside their premises.	
ICAO / IATA:	Can be shipped by air in accordance with International Civil Aviation Organization (ICAO), TI or International Air Transport Association (IATA), DGR Packing Instructions (PI) 965 Section IB appropriate of IATA DGR 60th (2019 Edition) for transportation.	(.
IMDG CODE:	The batteries are not restricted to IMDG Code 2018 Edition (Amdt 39-18) according to special provision 188.	0
DOT:	Other requirements for the US Department of Transportation (DOT) Subchapter C, Hazardous Materials Regulations if shipped in compliance with 49 CFR 173.185.	
ADR/ ADN:	Transport Requirements for United Nations Economic Commission for Europe (UNECE) ADR/ADN, Applicable as from 1 January 2019.	r
ests set out in Subsection 38.3 c	nsport each lithium cell and battery types must have passed the applicable of the UN Manual of Tests and Criteria.	
Section 15 – Regulatory	nsport each lithium cell and battery types must have passed the applicable of the UN Manual of Tests and Criteria.	
Section 15 – Regulatory Dangerous Goods Regulation Recommendations on the Tra	nsport each lithium cell and battery types must have passed the applicable of the UN Manual of Tests and Criteria. y Information	
Section 15 – Regulatory Dangerous Goods Regulation Recommendations on the Tra	Ansport each lithium cell and battery types must have passed the applicable of the UN Manual of Tests and Criteria.	
Section 15 – Regulatory Dangerous Goods Regulation Recommendations on the Tra Recommendations on the Tra International Air Transport As	Ansport each lithium cell and battery types must have passed the applicable of the UN Manual of Tests and Criteria.	
Section 15 – Regulatory Dangerous Goods Regulation Recommendations on the Tra Recommendations on the Tra International Air Transport As International Maritime Danger	Insport each lithium cell and battery types must have passed the applicable of the UN Manual of Tests and Criteria. Y Information Ins Ansport of Dangerous Goods-Model Regulations (20th revised edition) Ansport of Dangerous Goods-Manual of Tests and Criteria sociation (IATA)	
Section 15 – Regulatory Dangerous Goods Regulation Recommendations on the Tra Recommendations on the Tra International Air Transport As International Maritime Danger Technical Instructions for the	Ansport each lithium cell and battery types must have passed the applicable of the UN Manual of Tests and Criteria.	
Section 15 – Regulatory Dangerous Goods Regulation Recommendations on the Tra Recommendations on the Tra International Air Transport As International Maritime Danger Technical Instructions for the Classification and code of dar	Ansport each lithium cell and battery types must have passed the applicable of the UN Manual of Tests and Criteria.	
Section 15 – Regulatory Dangerous Goods Regulation Recommendations on the Tra Recommendations on the Tra International Air Transport As International Maritime Danger Technical Instructions for the Classification and code of dar	Ansport each lithium cell and battery types must have passed the applicable of the UN Manual of Tests and Criteria. Y Information ansport of Dangerous Goods-Model Regulations (20th revised edition) ansport of Dangerous Goods-Manual of Tests and Criteria sociation (IATA) rous Goods (IMDG Code 2018 Edition Amdt 39-18) Safe Transport of Dangerous Goods ngerous goods (GB 6944-2012) hication Standard (29 CFR 1910.1200)	
Section 15 – Regulatory Dangerous Goods Regulation Recommendations on the Tra Recommendations on the Tra International Air Transport As International Maritime Danger Technical Instructions for the Classification and code of dar 2012 OSHA Hazard Commun	Ansport each lithium cell and battery types must have passed the applicable of the UN Manual of Tests and Criteria. Y Information ansport of Dangerous Goods-Model Regulations (20th revised edition) ansport of Dangerous Goods-Manual of Tests and Criteria sociation (IATA) rous Goods (IMDG Code 2018 Edition Amdt 39-18) Safe Transport of Dangerous Goods ngerous goods (GB 6944-2012) hication Standard (29 CFR 1910.1200)	
Section 15 – Regulatory Dangerous Goods Regulation Recommendations on the Tra Recommendations on the Tra International Air Transport As International Maritime Danger Technical Instructions for the Classification and code of dan 2012 OSHA Hazard Commun Toxic Substance Control Act	Insport each lithium cell and battery types must have passed the applicable of the UN Manual of Tests and Criteria.	



Material Safety Data Sheet

Section 16 – Additional Information

MSDS creation date: 2019 Version: 1.0

Sample photo:



To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.

******End of report******

Report No.: TCT180815M004 Shenzhen TCT Testing Technology Co., Ltd. 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China Search Number: TCT180815M004C Search System: http://www.tct-lab.com/cn/search.asp Page 8 of 8