

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



L1N #1 1/2" 2 Hole Long Barrel Compression Lug Nsi Industries

Catalog Number	L1N
Manufacturer	Nsi Industries
Description	2 Hole Long Barrel Copper Compression Lug 1 Awg - 1/2" Bolt Long Barrel Copper Compression Lugs Are Produced From High Conductivity Copper Tubing. Allows Easy Inspection Of The Termination to Assure Complete Cable Insertion. Tin-Plated to Provide Corrosion and Low Contact Resistance. Marked With Die Index and Color Coded. Listed For 35KV Maximum When Properly Installed. Rated 600V. Culus 486A/B Listed. UL467 Listed On Sizes 6 Awg - 3/0 Awg. Temperature Rating 90 Degrees C.
Weight per unit	0.1100 (lbs/each)
Product Category	Large Terminals & Connectors
Features	
Cable Size	# 1 AWG (STR)
Material	Copper
Number of Holes	2
Stud Size	1/2
Voltage Rating	600 V
Warranty	1 YEAR
Material, Color, and Finish	
Color	Green
Finish	Tin Plated
Dimensions and Weight Size	L=4.29 - W=.750 - OD=.470 - ID=.360



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Description #1 1/2" 2 HOLE LONG BARREL COMPRESSION LUG extra long description NSI L1N CU CMP Lug Long 1 AWG Nema Features 2 Hole Long Barrel Copper Compression Lug 1 AWG - 1/2" Bolt Long Barrel Copper Compression Lugs are produced from high conductivity copper tubing. Allows easy inspection of the termination to assure complete cable insertion. Tin-plated to provide corrosion and low contact resistance. Marked with die index and color coded. Listed for 35KV maximum when properly installed. Rated 600V. CULus 486A/B Listed. UL47 Listed on sizes 6 AWG - 3/0 AWG. Temperature rating 90 degrees C. Long Description 2 Hole Long Barrel Copper Compression Lug a AWG - 1/2" Bolt Long Barrel Copper Compression Lug are produced from high conductivity copper tubing. Allows easy inspection of the termination to assure complete cable insertion. Tin-plated to provide corrosion and low contact resistance. Marked with die index and color coded. Listed for 35KV maximum when properly installed. Rated 600V. CULUs 486A/B Listed. UL47 Listed on sizes 6 AWG - 3/0 AWG. Temperature rating 90 degrees C. Product Type Cu CMP Lug Long 1 Awg Nema MTG Spac 5 psecial Features # 1 AWG (STR) - 1/2 Mounting Holes - 1 3/4 Hole Spacing Manufacturer Information Brand NSi GTIN 00662381035080 Category Description UPC 622381035080 Category Description Cong & Mech Lugs and Butt Splices Type Long Barrel - Two Hole Packaging Carton 1 Package 50 Meight Per each 0.11 Uses, Certifications, and Stan	Descriptions	
Features 2 Hole Long Barrel Copper Compression Lug 1 AWG - 1/2" Bolt Long Barrel Copper Compression Lugs are produced from high conductivity copper tubing. Allows easy inspection of the termination to assure complete cable insertion. Tin-plated to provide corrosion and low contact resistance. Marked with die index and color coded. Listed for 35KV maximum when properly installed. Rated 600V. cUlus 486A/B Listed. UL467 Listed on sizes 6 AWG - 3/0 AWG. Temperature rating 90 degrees C. Long Description 2 Hole Long Barrel Copper Compression Lug 1 AWG - 1/2" Bolt Long Barrel Copper Compression Lug 1 AWG - 1/2" Bolt Long Barrel Copper Compression Lug 3 AWG - 1/2" Bolt Long Barrel Copper Compression Lug 3 AWG - 1/2" Bolt Long Barrel Copper Compression Lug 3 AWG - 1/2" Bolt Long Barrel Copper Compression Lug 3 AWG - 1/2" Bolt Long Barrel Copper Compression Lug 3 AWG - 1/2" Bolt Long Barrel Copper Compression Lug 3 AWG - 1/2" Bolt Long Barrel Copper Compression Lug 3 AWG - 1/2" Bolt Long Barrel Copper Compression Lug 3 AWG - 1/2" Bolt Long Barrel Copper Compression Lug 4 AWG - 1/2" Bolt Long Barrel Copper Compression Lug 4 AWG - 1/2" Bolt Long Barrel Copper Compression Lug 4 AWG - 1/2" Bolt Long Barrel Copper Compression Lug 4 AWG - 1/2" Bolt Long Barrel Copper Cu CMP Lug Long 1 Awg Mema MTG Spac # 1 AWG (STR) - 1/2 Mounting Holes - 1 3/4 Hole Spacing Manufacturer Information Brand NSi GTIN O0662381035080 Category Description Long Barrel - Two Hole Peakaging Carton Comp & Mech Lugs and Butt Splices Type Long Barrel - Two Hole Package 50 So Weight Per each 0.11 Uses, Certifications, and Standards Application Terminate, Splice, Tap Power Connectors environmental conditions 90 C	Description	#1 1/2" 2 HOLE LONG BARREL COMPRESSION LUG
Long Barrel Copper Compression Lugs are produced from high conductivity copper tubing. Allows easy inspection of the termination to assure complete cable insertion. Tin-plated to provide corrosion and low contact resistance. Marked with die index and color coded. Listed for 35KV maximum when properly installed. Rated 600V. CULus 486A/8 Listed. UL467 Listed on sizes 6 AWG - 3/0 AWG. Temperature rating 90 degrees C. Long Description 2 Hole Long Barrel Copper Compression Lug 1 AWG - 1/2" Bolt Long Barrel Copper Compression Lugs are produced from high conductivity copper tubing. Allows easy inspection of the termination to assure complete cable insertion. Tin-plated to provide corrosion and low contact resistance. Marked with die index and color coded. Listed for 35KV maximum when properly installed. Rated 600V. cULus 486A/8 Listed. UL467 Listed on sizes 6 AWG - 3/0 AWG. Temperature rating 90 degrees C. Product Type Cu CMP Lug Long 1 Awg Nema MTG Spac Special Features # 1 AWG (STR) - 1/2 Mounting Holes - 1 3/4 Hole Spacing Manufacturer Information Brand NSi GTIN 00662381035080 UPC 662381035080 UPC 662381035080 UPC 662381035080 Taxonomies, Classifications, and Categories Category Description Comp & Mech Lugs and Butt Splices Type Long Barrel - Two Hole Package 50 Weight Per each 0.11 Uses, Certifications, and Standards Application Terminate, Splice, Tap Power Connectors environmental conditions 90 C Mounting 1/2 Mounting Holes	extra long description	NSI L1N CU CMP Lug Long 1 AWG Nema
Long Description2 Hole Long Barrel Copper Compression Lug 1 AWG - 1/2" Bolt Long Barrel Copper Compression Lugs are produced from high conductivity copper tubing. Allows easy inspection of the termination to assure complete cable insertion. Tin-plated to provide corrosion and low contact resistance. Marked with die index and color coded. Listed for 35KV maximum when properly installed. Rated 600V. cULus 486A/B Listed. UL467 Listed on sizes 6 AWG - 3/0 AWG. Temperature rating 90 degrees C.Product TypeCu CMP Lug Long 1 Awg Nema MTG SpacSpecial Features# 1 AWG (STR) - 1/2 Mounting Holes - 1 3/4 Hole SpacingManufacturer InformationBrandBrandNSiGTIN00662381035080UPC662381035080UPC662381035080Taxonomies, Classifications, and Categories Category DescriptionCarton1PackagingCarton1Package50Weight Per each0.11Uses, Certifications, and Standards ApplicationApplicationTerminate, Splice, Tap Power Connectors environmental conditions90 C Mounting1/2 Mounting Holes	Features	Long Barrel Copper Compression Lugs are produced from high conductivity copper tubing. Allows easy inspection of the termination to assure complete cable insertion. Tin-plated to provide corrosion and low contact resistance. Marked with die index and color coded. Listed for 35KV maximum when properly installed. Rated 600V. cULus 486A/B Listed. UL467 Listed on sizes
Special Features# 1 AWG (STR) - 1/2 Mounting Holes - 1 3/4 Hole SpacingManufacturer InformationBrandNSiGTIN00662381035080UPC662381035080Taxonomies, Classifications, and CategoriesCategory DescriptionComp & Mech Lugs and Butt SplicesTypeLong Barrel - Two HolePackagingCarton1Package50Weight Per each0.11Uses, Certifications, and StandardsApplicationTerminate, Splice, Tap Power Connectorsenvironmental conditions90 CMounting1/2 Mounting Holes	Long Description	2 Hole Long Barrel Copper Compression Lug 1 AWG - 1/2" Bolt Long Barrel Copper Compression Lugs are produced from high conductivity copper tubing. Allows easy inspection of the termination to assure complete cable insertion. Tin-plated to provide corrosion and low contact resistance. Marked with die index and color coded. Listed for 35KV maximum when properly installed. Rated 600V. cULus 486A/B Listed. UL467 Listed on sizes
Manufacturer InformationBrandNSiGTIN00662381035080UPC662381035080Taxonomies, Classifications, and CategoriesCategory DescriptionComp & Mech Lugs and Butt SplicesTypeLong Barrel - Two HolePackagingCarton1Package50Weight Per each0.11Uses, Certifications, and StandardsApplicationTerminate, Splice, Tap Power Connectorsenvironmental conditions90 CMounting1/2 Mounting Holes	Product Type	Cu CMP Lug Long 1 Awg Nema MTG Spac
BrandNSiGTIN00662381035080UPC662381035080Taxonomies, Classifications, and CategoriesCategory DescriptionComp & Mech Lugs and Butt SplicesTypeLong Barrel - Two HolePackagingCarton1Package50Weight Per each0.11Uses, Certifications, and StandardsApplicationTerminate, Splice, Tap Power Connectorsenvironmental conditions90 CMounting1/2 Mounting Holes	Special Features	# 1 AWG (STR) - 1/2 Mounting Holes - 1 3/4 Hole Spacing
GTIN00662381035080UPC662381035080Taxonomies, Classifications, and CategoriesCategory DescriptionComp & Mech Lugs and Butt SplicesTypeLong Barrel - Two HolePackagingICarton1Package50Weight Per each0.11Uses, Certifications, and StandardsApplicationTerminate, Splice, Tap Power Connectorsenvironmental conditions90 CMounting1/2 Mounting Holes	Manufacturer Information	
UPC662381035080Taxonomies, Classifications, and CategoriesCategory DescriptionComp & Mech Lugs and Butt SplicesTypeLong Barrel - Two HolePackagingICarton1Package50Weight Per each0.11Uses, Certifications, and StandardsApplicationTerminate, Splice, Tap Power Connectorsenvironmental conditions90 CMounting1/2 Mounting Holes	Brand	NSi
Taxonomies, Classifications, and CategoriesCategory DescriptionComp & Mech Lugs and Butt SplicesTypeLong Barrel - Two HolePackagingICarton1Package50Weight Per each0.11Uses, Certifications, and StandardsApplicationTerminate, Splice, Tap Power Connectorsenvironmental conditions90 CMounting1/2 Mounting Holes	GTIN	00662381035080
Category DescriptionComp & Mech Lugs and Butt SplicesTypeLong Barrel - Two HolePackaging1Carton1Package50Weight Per each0.11Uses, Certifications, and StandardsTerminate, Splice, Tap Power ConnectorsApplication90 CMounting1/2 Mounting Holes	UPC	662381035080
Category DescriptionComp & Mech Lugs and Butt SplicesTypeLong Barrel - Two HolePackaging1Carton1Package50Weight Per each0.11Uses, Certifications, and StandardsTerminate, Splice, Tap Power ConnectorsApplication90 CMounting1/2 Mounting Holes	Taxonomies, Classifications, and C	ategories
PackagingCarton1Package50Weight Per each0.11Uses, Certifications, and StandardsApplicationTerminate, Splice, Tap Power Connectorsenvironmental conditions90 CMounting1/2 Mounting Holes		-
Carton1Package50Weight Per each0.11Uses, Certifications, and StandardsApplicationTerminate, Splice, Tap Power Connectorsenvironmental conditions90 CMounting1/2 Mounting Holes	Туре	Long Barrel - Two Hole
Carton1Package50Weight Per each0.11Uses, Certifications, and StandardsApplicationTerminate, Splice, Tap Power Connectorsenvironmental conditions90 CMounting1/2 Mounting Holes	Packaging	
Weight Per each0.11Uses, Certifications, and StandardsTerminate, Splice, Tap Power ConnectorsApplicationTerminate, Splice, Tap Power Connectorsenvironmental conditions90 CMounting1/2 Mounting Holes		1
Weight Per each0.11Uses, Certifications, and StandardsTerminate, Splice, Tap Power ConnectorsApplicationTerminate, Splice, Tap Power Connectorsenvironmental conditions90 CMounting1/2 Mounting Holes	Package	50
ApplicationTerminate, Splice, Tap Power Connectorsenvironmental conditions90 CMounting1/2 Mounting Holes	0	0.11
ApplicationTerminate, Splice, Tap Power Connectorsenvironmental conditions90 CMounting1/2 Mounting Holes	Uses, Certifications, and Standards	
environmental conditions 90 C Mounting 1/2 Mounting Holes		
	Mounting	1/2 Mounting Holes
≞₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽	standard	UL486A/B, UL467 (8 AWG -3/0 AWG)