



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



LBY15SA 1/2" 90D Conduit Elbow *Crouse-Hinds*

| | |
|------------------|---|
| Catalog Number | LBY15SA |
| Manufacturer | Crouse-Hinds |
| Description | Conduit Elbow, 1/2 In Trade Size, Natural, Straight Connection Orientation, Threaded Connection, 0.34 LB/Ea |
| Weight per unit | 0.3400 (lbs/each) |
| Product Category | Aluminum |

Features

| | |
|------------|-----------------------------------|
| connection | Threaded |
| dimensions | 2.0000 IN X 2.0000 IN X 2.8100 IN |

Material, Color, and Finish

| | |
|--------|-----------|
| Finish | Untreated |
|--------|-----------|

Descriptions

| | |
|------------------------|---|
| Description | 1/2" 90D CONDUIT ELBOW |
| extra long description | CRS-H LBY15 SA 1/2 LBY AL ELBOW CVR |
| Features | <p>Crouse-Hinds series explosionproof unions are installed in rigid/IMC conduit systems to connect conduit to conduit, a conduit fitting, junction box or device enclosure. Expansion unions are also available, which allow for expansion and contraction of conduit and compensate for conduit cut too short. Available in a variety of materials, including stainless steel, to suit customer preferences. Explosionproof elbows allow for a 90° change in direction to the conduit run, or when terminating at a box or fit</p> |

Manufacturer Information

| | |
|-------|---------------------------|
| Brand | EATON CROUSE-HINDS SERIES |
| GTIN | 00782274277059 |
| UPC | 782274277059 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|-----------------------------|
| Category Description | HAZARDOUS LOCATION FITTINGS |
| Type | ELBOW |

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Package | 10 |
| Weight Per each | 0.34 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Enclosure

Class I Div 1 2 Group C D, Class II Div 1 Group E F G, Class II Div 2
Group F G, Class III

standard

UL 886, CSA C22.2