

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LCD414AL 4AWG 2HOLE Lug *Panduit Corporation*

Catalog Number	LCD414AL
Manufacturer	Panduit Corporation
Description	The LCD4-14A-L Copper Compression Connector Lug, Two-Hole, Standard Barrel, Has Color-Coded Barrels Marked With Panduit and Specified Competitor Die Index Numbers For Proper Crimp Die Selection. An Inspection Window Aids to Visually Assure Full Conductor Insertion, and The Tin-Plate Material Helps to Inhibit Corrosion. UI Listed and Csa Certified.
Weight per unit	
Product Category	
Features	
Material	Tin-Plated Copper
media	Yes
Number of Holes	2
Stud Size	1/4
Material, Color, and Finish	
Color	Gray
Dimensions and Weight	
Size	#4 — #3 AWG Code STR, #2 AWG Code SOL
Descriptions	
Description	4AWG 2HOLE LUG
extra long description	PAN LCD4-14A-L Pan-Lug™ LCD4-14A-L
Long Description	The LCD4-14A-L Copper Compression Connector Lug, two-hole, standard barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. An inspection window aids to visually assure full conductor insertion, and the tin-plate material helps to inhibit corrosion. UL Listed and CSA Certified.
Product Type	Pan-Lug™ LCD4-14A-L Comp. Lug, 4, Tin PLT Copper, STRT, Two
Special Features	Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 V
Manufacturer Information	
Brand	PANDUIT
GTIN	00074983383047
Manufacturers Part Number	LCD4-14A-L
UPC	074983383047



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories	
	Comp & Mech Lugs and Butt Splices
Туре	Compression Lug
Packaging	
Carton	1
Package	50
Weight Per each	0.0342
Uses, Certifications, and Standard	ds
Mounting	7/8
standard	CSA certified C22.2 No. 65-13, UL Listed to 486A-486B File

#E52164, NEBS Level 3