


Model

## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





## LED27T5H048GC850 27W Led T5HO 48" 50K GLS 3400LM

Keystone Technologies

4)				
Catalog Number	LED27T5H048GC850			
Manufacturer	Keystone Technologies			
Description	Linear Fluorescent Led Lamp, Linear, Instant Start Type; 45.2 Inch; UI (Canada and Us), UI, NSF/Ansi, Etl Approval; Food Equipment, Splash Zone, Dry and Damp Location Application; 0.69 Inch Diameter; 27 Watt Wattage; Led Lamp			
Weight per unit	- · · · · · · · · · · · · · · · · · · ·			
Product Category	20160824180628			
Features				
Beam Spread Angle	240 Degree			
Glass Finish	FROSTED			
Intensity	3400 Lumen			
Item	LED Lamp			
Wattage	27 Watt			
Material, Color, and Finish				
Base Type	G5 Miniature 2-Pin			
Color Rendering Index	80 A			
Color Temperature in Kelvin	5000			
Dimensions and Weight				
Diameter	0.69 Inch			
Length	45.2 Inch			
Descriptions				
Additional Information	RoHS Compliant; Shatter Proof Coated Glass; System Wattage 30 Watt; Efficacy 125 Lumen per Watt; Visible Light Area 325 Degree; Temperature -20 to 45 Deg C			
Commodity Description	Led Linear Fluorescent Straight, U-Shape & Circular Lamps			
Description	27W LED T5HO 48" 50K GLS 3400LM			
Long Description	LINEAR FLUORESCENT LED LAMP, LINEAR, INSTANT START TYPE; 45.2 INCH; UL (CANADA AND US), UL, NSF/ANSI, ETL APPROVAL; FOOD EQUIPMENT, SPLASH ZONE, DRY AND DAMP LOCATION APPLICATION; 0.69 INCH DIAMETER; 27 WATT WATTAGE; LED LAMP			
Manufacturer Information				
Brand	Keystone Technologies			
Manufacturers Part Number	KT-LED27T5HO-48GC-850-S			

800



Approval

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies,	Classi	fications,	and	Categories

Category Description	LED LINEAR STRAIGHT(Fluor replacement), U-SHAPE & CIRCULAR LAMPS		
Туре	Linear, Instant Start		
Packaging			
Carton	1		
Package	40		
Weight Per each	0.46		
Uses, Certifications, and Standar	rds		
Application	Food Equipment, Splash Zone, Dry and Damp Location		

UL (Canada and US), UL, NSF/ANSI, ETL