

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LPCC1 1A 600V TD Class CC Low Peak Fuse

Bussmann Fuses

Catalog Number	LPCC1
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class CC Fuse, LP-CC, Time-Delay, Dual-Element Current Limiting Fuse, 1 A, Rejection Style Fuse, Interrupting Rating Of 200 Ka At 600 Vac and 20 Ka At 300 VDC
Weight per unit	0.0200 (lbs/each)
Product Category	Current Limiting
Features	
amperage rating	1
connection	Ferrule End X Ferrule End
dimensions	0.4100 IN X 0.4100 IN X 1.5000 IN
element	Dual
Fuse Class	Class CC
interrupt rating	200 kAIC at 600 Vac20 kAIC at 300 Vdc
Material	Melamine Tube
media	Yes
Response Time	12 S at 200%
Voltage Rating	600 Vac, 300 Vdc
Dimonsions and Woight	

Dimensions and Weight

Size 13/32 In Diameter X 1-1/2 In Length



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

)es		

BUSS LP-CC-1 LOW PEAK CC TIME DELAY
DOGGET - GG-T LOW T LAIK GG THVIL DLLAT
Bussmann's Class CC fuses set the standard in Class CC fuse performance in the industry. Recognized for their superior performance, Bussmann has the right product for your circuit and equipment protection needs. These branch circuit rated, 600v, 200,000a IR fuses offer exceptional protection in the smallest package of any UL class of fuses. Choose from the ultimate protection provided by our Low Peak LP-CC fuses, the time delay of our FNQ-R's for your control transformer and similar control applications or
Eaton Bussmann Series Class CC fuse, LP-CC, time-delay, dual-element current limiting fuse, 1 A, rejection style fuse, interrupting rating of 200 kA at 600 Vac and 20 kA at 300 Vdc
Low Peak CC Time Delay
Non-Indicating

Manufacturer Information

Brand	Eaton Bussmann series
GTIN	00051712180436
Manufacturers Part Number	LP-CC-1
UPC	051712180436

Taxonomies, Classifications, and Categories

Category Description	MIDGET FUSES
Туре	FUSE

Packaging

Carton	10
Weight Per each	0.02

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked,RoHS Compliant