

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LPJ20SPI Buss LPJ-20SPI Low-Peak Class J Ind Bussmann Fuses

Catalog Number	LPJ20SPI
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class J Fuse, LPJ, Time-Delay,
	Dual-Element Current Limiting Fuse, 20 A, Indicating Fuse,
	Interrupting Rating Of 300 Ka At 600 Vac
Weight per unit	
Product Category	Small Dimension Fuses
Features	
amperage rating	20
connection	Ferrule End X Ferrule End
dimensions	2.2500 IN X 0.8100 IN X 0.8100 IN
element	
Fuse Class	
interrupt rating	100 kAIC Vdc300 kAIC at 600 Vac
media	Yes
Response Time	10 sec at 500%
Voltage Rating	600 Vac, 300 Vdc
Dimensions and Weight	
Size	0.81 In Diameter X 2.25 In Length
Descriptions	
Description	BUSS LPJ-20SPI LOW-PEAK CLASS J IND
extra long description	BUSS LPJ-20SPI LOW-PEAK CLASS J IND
Features	Bussmann's UL Class J fuse products extend both our Low-Peak
	family of products with our LPJ_SP and LPJ_SPI dual-element,
	time-delay fuses as well as our Limitron line offering fast-acting
	JKS fuses. The LPJ fuses provide industry leading 300,000 amp
	interrupting rating at 600Vac RMS Sym and 100kA Vdc while
	delivering a minimum of 10 seconds of 500 percent rated current
	ride-through performance which is ideal for sizing of high inrush
	loads. The LPJ products are available with optional permanent
Long Description	replace fu Eaton Bussmann Series Class J fuse, LPJ, time-delay, dual-element
Long Description	current limiting fuse, 20 A, indicating fuse, interrupting rating of
	300 kA at 600 Vac
Product Type	Low-Peak Class J Indicating T/D
Special Features	Non-indicating, High in-rush current motor protection
- Contractor and Cont	



ELLIOT ELECTRIC SUPPLY Mar Deliver Lower Cost Quality Products, & Personal Service 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information	
Brand	Bussmann Fuses
Manufacturers Part Number	LPJ-20SPI
Taxonomies, Classifications, and Cat	tegories
Category Description	GLASS FUSES (and ceramic)
Туре	FUSE
Packaging	
Carton	1
Weight Per each	0.11
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked, RoHS Compliant