

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LPSRK20SP 20A 600V TD Dual Elem Class RK1 Low Peak Fuse Bussmann Fuses

Catalog Number	LPSRK20SP
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class RK1 Fuse, LPS-RK, Time-Delay, Dual-Element, Current Limiting Fuse, 20 A, Non-Indicating Fuse, Interrupting Rating Of 300 Ka At 600 Vac and 100 Ka At 300 VDC
Weight per unit	0.1600 (lbs/each)
Product Category	Dual Element
eatures	
amperage rating	20
class	Class RK1
connection	
dimensions	5.0000 IN X 0.8100 IN X 0.8100 IN
element	Dual
Fuse Class	Class RK1
interrupt rating	100 kAIC at 300 Vdc300 kAIC at 600 Vac
media	Yes
Response Time	
Voltage Rating	600 Vac, 300 Vdc
Dimensions and Weight	
Size	0.81 In Diameter X 5.00 In Length
Descriptions	
Description	20A 600V TD DUAL ELEM CLASS RK1 LOW PEAK FUSE
extra long description	BUSS LPS-RK-20SP LOW-PEAK DUAL ELEM
Features	Bussmann's UL Class RK1 fuse offering includes the industry's most recognized Low-Peak dual-element, current-limiting, time-delay fuses (LPN-RK and LPS-RK) which are also available with optional indication on select ratings (see product data sheet). Complementing the Low-Peak product offering is Bussmann's Limitron family of fast-acting fuses (KTN-R, KTS-R, KWN-R and KWS-R) fuses.
Long Description	Eaton Bussmann Series Class RK1 fuse, LPS-RK, time-delay, dual-element, current limiting fuse, 20 A, non-indicating fuse, interrupting rating of 300 kA at 600 Vac and 100 kA at 300 Vdc
Product Type	Low-Peak Dual Element
Special Features	Electrically Isolated End Cap



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Inform

Brand	Eaton	
GTIN	00051712548342	
Manufacturers Part Number	LPS-RK-20SP	
UPC	051712548342	

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSE

Packaging

onag.i.g	
Carton	10
Weight Per each	0.16

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked