

Type

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

LS7.9520A 20.5" Unctd SS Cable Tie Abb Installation Products, Inc

Catalog Number	LS7.9520A
Manufacturer	Abb Installation Products, Inc
Description	Ball-Lock 304 Stainless Steel Cable Tie, Uncoated, For
	Temperatures Up to 300 Degrees Celsius (572 F) For Indoor and
	Outdoor Applications, Suitable For High Temperature
	Environments, UI/En/CSA62275 Type 2S Rated For Ah-1 Plenum,
	Length Of 520MM (20.5 Inches), Width Of 7.75MM (0.305 Inches), Thickness Of 0.25MM (0.01 Inches), Tensile Strength
	Rating Of 2002 Newtons (450 Pounds)
Weight per unit	0.0200 (lbs/each)
Product Category	Cable Ties & Wraps
Features	
Tensile Strength	450;2002
ŭ	430,2002
Dimensions and Weight	20.5
Length	20.5
Thickness	0.01
Width	0.305
Descriptions	
Description	20.5" UNCTD SS CABLE TIE
extra long description	ABB LS-7.9-520A CABLE TIE 302/304 S
Long Description	Ball-Lock 304 Stainless Steel Cable Tie, Uncoated, for
	Temperatures up to 300 Degrees Celsius (572 F) for Indoor and
	Outdoor Applications, Suitable for High Temperature
	Environments, UL/EN/CSA62275 Type 2S Rated for AH-1 Plenum
	Length of 520mm (20.5 Inches), Width of 7.75mm (0.305 inches)
	Thickness of 0.25mm (0.01 Inches), Tensile Strength Rating of 2002 Newtons (450 Pounds)
Product Type	
3.	Ouble Tie 302/304 331 430EB 21 Bui
Manufacturer Information	Ty Dan
Brand GTIN	00707010040004
Manufacturers Part Number	LS-7.9-520A
LIDO	70/010040004
Taxonomies, Classifications, and (•
Category Description	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps

Stainless Steel



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Availability	
minimum qty	50
Packaging	
Carton	50
Weight Per each	0.02
Uses, Certifications, and Standards	
standard	UL E49405