

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

LT12545 1-1/4" 45 Crouse-Hinds	D LT Conn
Catalog Number	LT12545
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC, 45° Angle, Non-Insulated, Malleable Iron, 1-1/4"
Weight per unit	0.9500 (lbs/each)
Product Category	Liquid Tight Fittings
Features	
connection	Threaded
dimensions	3.5000 IN X 2.2500 IN X 3.5000 IN
installation type	THREADED
Material, Color, and Finish	
Color	MALLEABLE IRON
Descriptions	
Description	1-1/4" 45D LT CONN
extra long description	MIDWEST LT12545 1 1/4 LT 45 DEGREE
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are
	designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs. To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC,
	45° angle, Non-insulated, Malleable iron, 1-1/4"
Product Type	1 1/4 LT 45 Degree Conn
Manufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00784564451255
Manufacturers Part Number	LT12545
UPC	784564451255
Taxonomies, Classifications, and C	Categories
Category Description	
Туре	Liquidtight connector
Trade Size	
Trade Size	1 1/4 in



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packa	nuina
	ignig

гаскаушу	
Carton	
Weight Per each	0.95
Uses, Certifications, and Standa	rds
Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22.23