

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## LT250G 2-1/2" LT Conn Ground 1/0 Crouse-Hinds

Crouse-Hinds	
Catalog Number	LT250G
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC, Straight, Aluminum Ground Lug, Non-Insulated, #1/0-8 Awg Lug Size, Malleable Iron, 2-1/2"
Weight per unit	3.0 (lbs/each)
Product Category	Liquid Tight Fittings
Features	
connection	Threaded
dimensions	3.1900 IN X 4.0000 IN X 4.0000 IN
installation type	THREADED
Material, Color, and Finish	
Color	MALLEABLE IRON
Descriptions	
Description	2-1/2" LT CONN GROUND 1/0
extra long description	MIDWEST LT250G 2 1/2 LT CONN GRND 1
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs. To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC, Straight, Aluminum ground lug, Non-insulated, #1/0-8 AWG lug size, Malleable iron, 2-1/2"
Product Type	2 1/2 LT Conn GRND 1/0
Special Features	With 8 To 1/0 AWG Aluminum Grounding Lug
Manufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00784564260079
Manufacturers Part Number	LT250G
UPC	784564260079

## **Taxonomies, Classifications, and Categories**

Category Description	METALLIC FITTINGS
Type	Liquidtight connector



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Trade Size Trade Size	2 1/2 in
Packaging Carton	1
Weight Per each	2.95
<b>Uses, Certifications, and Standards</b>	
Application	Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22.2