



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## LT30090G 3" 90D LT Conn Ground 1/0

*Crouse-Hinds*

Catalog Number	LT30090G
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC, 90° Angle, Aluminum Ground Lug, Non-Insulated, #1/0-8 Awg Lug Size, Malleable Iron, 3"
Weight per unit	12.8 (lbs/each)
Product Category	Liquid Tight Fittings

### Features

connection	Threaded
dimensions	10.9400 IN X 4.1900 IN X 10.9400 IN
installation type	THREADED

### Material, Color, and Finish

Color	MALLEABLE IRON
-------	----------------

### Descriptions

Description	3" 90D LT CONN GROUND 1/0
extra long description	MIDWEST LT30090G 3 LT 90 DEGREE CON
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs. To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC, 90° angle, Aluminum ground lug, Non-insulated, #1/0-8 AWG lug size, Malleable iron, 3"
Product Type	3 LT 90 Degree Conn GRND 1/0

### Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00784564260482
Manufacturers Part Number	LT30090G
UPC	784564260482

### Taxonomies, Classifications, and Categories

Category Description	METALLIC FITTINGS
Type	Liquidtight connector



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Trade Size

Trade Size ..... 3 in

## Packaging

Carton ..... 1

Weight Per each ..... 12.8

## Uses, Certifications, and Standards

Application ..... Commercial / Institutional Buildings / Structures - Commercial /  
Institutional Buildings / Structures - Other

standard ..... UL 467, UL 514B, CSA C22.42