


ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





LT3845 3/8" 45D LT Conn Crouse-Hinds

Catalog Number	LT3845
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC, 45° Angle, Non-Insulated, Malleable Iron, 3/8"
Weight per unit	0.1800 (lbs/each)
Product Category	Liquid Tight Fittings
aturos	

Features

connection	Threaded
dimensions	2.4400 IN X 1.1300 IN X 1.1300 IN
installation type	THREADED

Material, Color, and Finish

Color MALLEABLE IRON	
----------------------	--

Descriptions

Description	3/8" 45D LT CONN
extra long description	MIDWEST LT3845 3/8 LT 45 DEGREE CON
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs. To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC, 45° angle, Non-insulated, Malleable iron, 3/8"
Product Type	3/8 LT 45 Degree Conn

Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00784564450388
Manufacturers Part Number	LT3845
UPC	784564450388

Taxonomies, Classifications, and Categories

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Туре	Liquidtight connector

Trade Size

Trade Size 3/8/2015	
---------------------	--



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941

We Deliver...Lower Cost. Quality Products. & Personal Service

Fax: 936-560-4685

 VVC DCIIVCILOWCI	OUSI,	Quanty	 oddoto,	αı	Cisonai	OCI VICC

Packaging	
Carton	1
Package	25
Weight Per each	0.18
Uses, Certifications, and Standards	
Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22.7