

ELLIOTT ELECTRIC SUPPLY We Deliver Lower Cost. Quality Products, & Personal Service 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LT40045 4" 45D LT Conn Crouse-Hinds

Catalog Number	LT40045
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC, 45° Angle, Non-Insulated, Malleable Iron, 4"
Weight per unit	15.9 (lbs/each)
	Liquid Tight Fittings
Features	
connection	Threaded
dimensions	12.3100 IN X 5.7500 IN X 12.3100 IN
installation type	THREADED

Material, Color, and Finish

Color MALLEABLE IRON	
----------------------	--

Descriptions

Description	4" 45D LT CONN
extra long description	MIDWEST LT40045 4 LT 45 DEGREE CONN
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs. To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC, 45° angle, Non-insulated, Malleable iron, 4"
Product Type	4 LT 45 Degree Conn

Manufacturer Information

Brand	Eaton
GTIN	00784564454003
Manufacturers Part Number	LT40045
UPC	784564454003

Taxonomies, Classifications, and Categories

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Туре	Liquidtight connector

Trade Size

Trade Size	4 in
------------	------



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	15.9
Uses, Certifications, and Standa	ards
Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22.47