

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## LT40045G 4" 45D LT Conn Ground 3/0 Crouse-Hinds

Taxonomies, Classifications, and Categories
Category Description META

Type

Crouse-Hinds	
Catalog Number	LT40045G
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC, 45° Angle, Aluminum Ground Lug, Non-Insulated, #3/0-6 Awg Lug Size, Malleable Iron, 4"
Weight per unit	15.4 (lbs/each)
Product Category	Liquid Tight Fittings
Features	
connection	Threaded
dimensions	8.0000 IN X 17.2000 IN X 6.8000 IN
installation type	THREADED
Material, Color, and Finish	
Color	MALLEABLE IRON
Descriptions	
Description	4" 45D LT CONN GROUND 3/0
extra long description	MIDWEST LT40045G 4 LT 45 DEGREE CON
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs. To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC, 45° angle, Aluminum ground lug, Non-insulated, #3/0-6 AWG lug size, Malleable iron, 4"
Product Type	4 LT 45 Degree Conn GRND 3/0
Special Features	With 6 To 3/0 AWG Aluminum Grounding Lug
Manufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00784564260307
Manufacturers Part Number	LT40045G
UPC	784564260307

METALLIC FITTINGS

Liquidtight connector



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Trade Size Trade Size	4 in
Packaging Carton	1
Weight Per each	15.35
<b>Uses, Certifications, and Standards</b>	
Application	Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22,48