



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



M4250075342 Sleeve 0.25IN Dia Black O

Brady Worldwide, Inc.

| | |
|------------------|---|
| Catalog Number | M4250075342 |
| Manufacturer | Brady Worldwide, Inc. |
| Description | Permasleeve® Heat-Shrink Labels Polyolefin 0.439"H X 0.75"W BK/WT 0.25"Dia |
| Weight per unit | N/A |
| Product Category | Tools & Testers |

Features

| | |
|-------------------|-------------------------|
| Material | Heat-shrink Polyolefin |
| Number of Markers | 80 |
| Quantity | Cartridge of 80 Each |
| Shrink Ratio | 3:1 |
| Temperature Range | -67 °F - 275 °F |
| Wire Size | 0.25 in Dia x 0.75 in W |

Material, Color, and Finish

| | |
|--------------|----------------|
| Finish | Matte |
| Legend Color | Black on White |

Dimensions and Weight

| | |
|----------|------------------------|
| Diameter | 0.25 |
| Height | 0.439 in |
| Size | 0.439 in H x 0.75 in W |
| Width | 0.75 in |

Descriptions

| | |
|------------------------|---|
| Description | SLEEVE 0.25IN DIA BLACK O |
| extra long description | BRADY M4-250-075-342 Sleeve 0.25in |
| Features | Permanently mark wires with the durable PermaSleeve® PS heat-shrink polyolefin sleeve label material (B-342). Designed for use with a durable Brady handheld label printer. |
| Long Description | PermaSleeve® Heat-Shrink Labels Polyolefin 0.439"H x 0.75"W BK/WT 0.25"Dia |
| Product Type | Sleeve 0.25IN Dia Black On White 0.75in |
| Special Features | Heat Shrink |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | Brady® |
| GTIN | 00888434591475 |
| Manufacturers Part Number | M4-250-075-342 |
| UPC | 888434591475 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Type SLEEVE

Packaging

Carton 1

Weight Per each 0

Uses, Certifications, and Standards

Application Wire and Cable Labeling

standard ASTM D 2671;ASTM E 162;ASTM E 662;ASTM G
155;MIL-STD-202;SAE-AMS-DTL-23053;SAE-AS-81531;UL
Recognized