


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





MACL153MBR Maestro 150W Led Multi Brown

Catalog Number	MACL153MBR
Manufacturer	Lutron
Description	Maestro Led+ Multiloc, Ed Box Brown
Weight per unit	0.4000 (lbs/each)
	Lighting Dimmers
itures	

Features

Connection Type	Screw Terminal
insulation	Plastic
Poles	1
Switch Type	Tapswitch
Voltage Rating	120
Wattage	600

Material, Color, and Finish

Finish	Gloss
A . I A A A A A A A A A A A A A A A A A	

Dimensions and Weight

A1	1 (0 001110 75
C170	1 60 v 7 01·110 v 7b
Size	4.69 x 2.94;119 x 75
. Y. i.= . Y	

Descriptions

Description	MAESTRO 150W LED MULTI BROWN
extra long description	LUT MACL-153M-BR MAESTRO LED+ MULTI
Features	The Maestro LED+ dimmer switch provides optimal dimming performance of LED bulbs. This dimmer switch works with up to 150-Watt of dimmable LED/CFL or 600-Watt of incandescent/halogen, allowing you to control multiple bulb types on the same circuit. It is designed to control a broad range of dimmable LED and CFL bulbs from a variety of brands including Philips, Cree, GE, EcoSmart and Lighting Science. Use the rocker to adjust the light level for any activity or set the preset level to ensure lights always t
Long Description	Maestro LED+ Multiloc, Ed Box Brown
Product Type	Maestro Led+ Multiloc Ed Box Brown
Special Features	Controls dimmable 150 W LED/CFL (screw-base) or 600 W incandescent/halogen loads. Provides true dimming from each location (with companion dimmers). Provides reliable dimming of dimmable LEDs/CFLs, as well as halogens and incandescents.



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

	N	lanui	facturer I	Information
--	---	-------	------------	-------------

Brand	Lutron
GTIN	00784276010719
Manufacturers Part Number	MACL-153M-BR
UPC	784276010719

Taxonomies, Classifications, and Categories

Category Description	Residential dimmers, motion sensors, controls, & photo cells
Туре	Digital fade dimmer, multi-location/3-way/single-pole

Packaging

Carton	1
Weight Per each	0.4

Uses, Certifications, and Standards

Application	Lighting Control
Enclosure	Plastic
environmental conditions	0 to 90% humidity, non-condensing. Indoor use only.
Mounting	WALLBOX
standard	UL, CSA, NOM