

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



MC122WG1000 12-2 WG MC Sol BK/WH/GN Alu Armor 1000' Southwire Company

Manufacturer Description Southwire Armorlite Type MC Cable is Constructed With Soft-Drawn Copper Type THHN/THWN-2 Conductors Rated 90ŰC Dry and A Bare Copper Grounding Conductor For Sizes 1/0 Awg and Larger. The Conductors Are Cabled Together and A Binder Tape Bearing The Print Legend Is Wirapped Around The Assembly. Aluminum Interlocking Armor is Applied Over The Assembly. Also Available in Steel. Conductors Are Black With Phase Identification. Colors Available Upon Request With Economic Order Quantity. Weight per unit O.1050 (lbs/ft) Product Category Wire Features Conductor Size 12 media Yes Number of Conductors 2 outside diameter 0.4746 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 1000 Description Description 12-2 WG MC SOL BK/WH/GN ALU ARMOR 1000' extra long description SWC 68580002 Armorlite Type MC Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly.	Catalog Number	MC122WG1000	
Soft-Drawn Copper Type THHN/THWN-2 Conductors Rated 90ŰC Dry and A Bare Copper Grounding Conductor For Sizes 1/0 Awg and Larger. The Conductors Are Cabled Together and A Binder Tape Bearing The Print Legend is Wrapped Around The Assembly. Aluminum Interlocking Armor Is Applied Over The Assembly. Also Available in Steel. Conductors Are Black With Phase Identification. Colors Available Upon Request With Economic Order Quantity. Weight per unit 0.1050 (lbs/ft) Product Category Wire Features Conductor Size 12 media Yes Number of Conductors 2 outside diameter 0.4746 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 1000 Descriptions Description 12-2 WG MC SOL BK/WH/GN ALU ARMOR 1000' extra long description SWC 68580002 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rate 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are abled together and a binder tape bearing the print legend is wrapped around the assembly. Also available in steel. Conductors are applied over the assembly. Also available upon request with economic order quantity.	_	Southwire Company	
Weight per unit Product Category Wire Features Conductor Size 12 media Yes Number of Conductors 2 outside diameter Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 1000 Descriptions Description 22-2 WG MC SOL BK/WH/GN ALU ARMOR 1000' extra long description SWC 68580002 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Description	Southwire Armorlite Type MC Cable Is Constructed With Soft-Drawn Copper Type THHN/THWN-2 Conductors Rated 90°C Dry and A Bare Copper Grounding Conductor For Sizes 1/0 Awg and Larger. The Conductors Are Cabled Together and A Binder Tape Bearing The Print Legend Is Wrapped Around The Assembly. Aluminum Interlocking Armor Is Applied Over The Assembly. Also Available In Steel. Conductors Are Black With Phase Identification. Colors Available Upon Request With Economic	
Features Conductor Size Mumber of Conductors Outside diameter Voltage Rating Outside diameter Outs	Weight per unit		
Conductor Size media Yes Number of Conductors 2 outside diameter 0.4746 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 1000 Descriptions Description 12-2 WG MC SOL BK/WH/GN ALU ARMOR 1000' extra long description SWC 68580002 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	• .		
Conductor Size media Yes Number of Conductors 2 outside diameter 0.4746 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 1000 Descriptions Description 12-2 WG MC SOL BK/WH/GN ALU ARMOR 1000' extra long description SWC 68580002 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Features		
Number of Conductors outside diameter 0.4746 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 1000 Descriptions Description 12-2 WG MC SOL BK/WH/GN ALU ARMOR 1000' extra long description SwC 68580002 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.		12	
outside diameter Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 1000 Descriptions Description 12-2 WG MC SOL BK/WH/GN ALU ARMOR 1000' extra long description SWC 68580002 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	media	Yes	
Waterial, Color, and Finish Conductor Material CU Dimensions and Weight Length 1000 Descriptions Description 12-2 WG MC SOL BK/WH/GN ALU ARMOR 1000' extra long description Swc 68580002 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Number of Conductors	2	
Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 1000 Descriptions Description Description Secription Secription	outside diameter	0.4746	
Conductor Material Dimensions and Weight Length 1000 Descriptions Description 12-2 WG MC SOL BK/WH/GN ALU ARMOR 1000' extra long description SWC 68580002 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Voltage Rating	600V	
Descriptions Description Description Description Description Description Description Description 12-2 WG MC SOL BK/WH/GN ALU ARMOR 1000' SWC 68580002 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Material, Color, and Finish Conductor Material	CU	
Description extra long description SWC 68580002 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Dimensions and Weight Length	1000	
Description extra long description SWC 68580002 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Descriptions		
extra long description SWC 68580002 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	-	12-2 WG MC SOL BK/WH/GN ALU ARMOR 1000'	
soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.		SWC 68580002 Armorlite Type MC	
Product Type Armorlite Type MC	•	soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification.	
	Product Type	Armorlite Type MC	



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	Flexible Conduit
GTIN	00032886347160
Manufacturers Part Number	68580002
UPC	032886347160

Taxonomies, Classifications, and Categories

Category Description	BX & MC
Type	MC

Availability

,	
Status	Inactive

Packaging

Carton	1000	
Weight	103.516	
Weight Per foot	0.105	