

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

MC122WGBL 12/2 WG MC BL/WH/GN Alu Armor 250' Southwire Company

Manufacturer Description Southwire Armorlite Type MC Cable Is Constructed With Soft-Drawn Copper Type THHN/THWN-2 Conductors Rated 90ŰC Dry and A Bare Copper Grounding Conductor For Sizes 1/0 Awg and Larger. The Conductors Are Cabled Together and A Binder Tape Bearing The Print Legend Is Wrapped Around The Assembly. Aluminum Interlocking Armor Is Applied Over The Assembly. Aluminum Interlocking Armor Is Applied Over The Assembly. Also Available In Steel. Conductors Are Black With Phase Identification. Colors Available Upon Request With Economic Order Quantity. Weight per unit 0.1150 (lbs/ft) Product Category Wire Features Conductor Size 12 media Yes Number of Conductors 2 outside diameter 0.4746 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/2 WG MC BL/WH/GN ALU ARMOR 250' extra long description SWC 68948901 Armorlite Type MC Long Description Southwire Armorlite Type MC Long Description Fize Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape	Catalog Number	MC122WGBL	
Description Southwire Armorlite Type MC Cable Is Constructed With Soft-Drawn Copper Type THHN/THWN-2 Conductors Rated 90ŰC Dry and A Bare Copper Grounding Conductor For Sizes 1/0 Awg and Larger. The Conductors Are Cabled Together and A Binder Tape Bearing The Print Legend Is Wrapped Around The Assembly. Aluminum Interlocking Armor Is Applied Over The Assembly. Aluminum Interlocking Armor Is Applied Over The Assembly. Also Available In Steel. Conductors Are Black With Phase Identification. Colors Available Upon Request With Economic Order Quantity. Weight per unit 0.1150 (lbs/ft) Product Category Wire Features Conductor Size 12 media Yes Number of Conductors 2 outside diameter 0.4746 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/2 WG MC BL/WH/GN ALU ARMOR 250' extra long description SWC 68948901 Armorlite Type MC Long Description Fundamental Colors and Interpretation of the Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape	3		
Dry and A Bare Copper Grounding Conductor For Sizes 1/0 Awg and Larger. The Conductors Are Cabled Together and A Binder Tape Bearing The Print Legend Is Wrapped Around The Assembly. Aluminum Interlocking Armor Is Applied Over The Assembly. Also Available In Steel. Conductors Are Black With Phase Identification. Colors Available Upon Request With Economic Order Quantity. Weight per unit 0.1150 (lbs/ft) Product Category Wire Features Conductor Size 12 media Yes Number of Conductors 2 outside diameter 0.4746 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/2 WG MC BL/WH/GN ALU ARMOR 250' extra long description SWC 68948901 Armorlite Type MC Long Description Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90Å*C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape	Description	• •	
and Larger. The Conductors Are Cabled Together and A Binder Tape Bearing The Print Legend Is Wrapped Around The Assembly. Aluminum Interlocking Armor Is Applied Over The Assembly. Also Available In Steel. Conductors Are Black With Phase Identification. Colors Available Upon Request With Economic Order Quantity. Weight per unit O.1150 (lbs/ft) Product Category Wire Features Conductor Size 12 media Yes Number of Conductors 2 outside diameter 0.4746 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Description Oescription Succ 68948901 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90A°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape	·	· · · · · · · · · · · · · · · · · · ·	
Tape Bearing The Print Legend Is Wrapped Around The Assembly. Aluminum Interlocking Armor Is Applied Over The Assembly. Also Available In Steel. Conductors Are Black With Phase Identification. Colors Available Upon Request With Economic Order Quantity. Weight per unit 0.1150 (lbs/ft) Product Category Wire Features Conductor Size 12 media Yes Number of Conductors 2 outside diameter 0.4746 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Description 12/2 WG MC BL/WH/GN ALU ARMOR 250' extra long description Such Wire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape		Dry and A Bare Copper Grounding Conductor For Sizes 1/0 Awg	
Aluminum Interlocking Armor Is Applied Over The Assembly. Also Available In Steel. Conductors Are Black With Phase Identification. Colors Available Upon Request With Economic Order Quantity. Weight per unit 0.1150 (lbs/ft) Product Category Wire Features Conductor Size 12 media Yes Number of Conductors 2 outside diameter 0.4746 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Descriptions Description 12/2 WG MC BL/WH/GN ALU ARMOR 250' extra long description SWC 68948901 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape		· · · · · · · · · · · · · · · · · · ·	
Available In Steel. Conductors Are Black With Phase Identification. Colors Available Upon Request With Economic Order Quantity. Weight per unit 0.1150 (lbs/ft) Product Category Wire Features Conductor Size 12 media Yes Number of Conductors 2 outside diameter 0.4746 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/2 WG MC BL/WH/GN ALU ARMOR 250' extra long Description SWC 68948901 Armorlite Type MC Long Description Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape			
Identification. Colors Available Upon Request With Economic Order Quantity. Weight per unit 0.1150 (lbs/ft) Product Category Wire			
Weight per unit 0.1150 (lbs/ft) Product Category Wire Features Conductor Size 12 media Yes Number of Conductors 2 outside diameter 0.4746 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/2 WG MC BL/WH/GN ALU ARMOR 250' extra long description SWC 68948901 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape			
Weight per unit Product Category Wire Features Conductor Size Media Yes Number of Conductors 2 outside diameter Voltage Rating Weight Conductor Material Cu Dimensions and Weight Length Description Description Such All ARMOR 250' extra long description Such Wall Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape		0.10	
Features Conductor Size 12 media Yes Number of Conductors 2 outside diameter 0.4746 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/2 WG MC BL/WH/GN ALU ARMOR 250' extra long description SWC 68948901 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape	Weight per unit	•	
Features Conductor Size 12 media Yes Number of Conductors 2 outside diameter Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/2 WG MC BL/WH/GN ALU ARMOR 250' extra long description SwC 68948901 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape	• .		
Conductor Size 12 media Yes Number of Conductors 2 outside diameter 0.4746 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/2 WG MC BL/WH/GN ALU ARMOR 250' extra long description SWC 68948901 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape	J,		
Mumber of Conductors 2 outside diameter 0.4746 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/2 WG MC BL/WH/GN ALU ARMOR 250' extra long description SWC 68948901 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape		12	
Number of Conductors outside diameter O.4746 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/2 WG MC BL/WH/GN ALU ARMOR 250' extra long description SWC 68948901 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape			
outside diameter Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/2 WG MC BL/WH/GN ALU ARMOR 250' extra long description SWC 68948901 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape			
Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/2 WG MC BL/WH/GN ALU ARMOR 250' extra long description SWC 68948901 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape			
Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/2 WG MC BL/WH/GN ALU ARMOR 250' extra long description SWC 68948901 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape			
Conductor Material Dimensions and Weight Length 250 Descriptions Description 12/2 WG MC BL/WH/GN ALU ARMOR 250' extra long description SWC 68948901 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape			
Dimensions and Weight Length 250 Descriptions Description 12/2 WG MC BL/WH/GN ALU ARMOR 250' extra long description SWC 68948901 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape		CH	
Length 250 Descriptions Description 12/2 WG MC BL/WH/GN ALU ARMOR 250' extra long description SWC 68948901 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape			
Descriptions Description Description 12/2 WG MC BL/WH/GN ALU ARMOR 250' extra long description SWC 68948901 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape	_	250	
Description 12/2 WG MC BL/WH/GN ALU ARMOR 250' extra long description SWC 68948901 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape		250	
extra long description SWC 68948901 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape	-	40 /0 INC NAC DI /IN/II /ONI ALLI ADMOD OFOI	
Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape			
soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape		• •	
dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape	Long Description	31	
and larger. The conductors are cabled together and a binder tape		, , , , , , , , , , , , , , , , , , , ,	
· · · · · · · · · · · · · · · · · · ·			
Dealling the billit legeth is wrapped around the assembly.		bearing the print legend is wrapped around the assembly.	
Aluminum interlocking armor is applied over the assembly. Also			
available in steel. Conductors are black with phase identification.		· · · · · · · · · · · · · · · · · · ·	
Colors available upon request with economic order quantity.		Colors available upon request with economic order quantity.	
Product Type Armorlite Type MC	Product Type	Armorlite Type MC	



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Brand	Copper
GTIN	00032886347535
Manufacturers Part Number	68948901
UPC	032886347535

Taxonomies, Classifications, and Categories

Category Description	BX & MC	
Type	MC	

Packaging

Carton	250	
Weight	25.879	
Weight Per foot	0.115	