

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

MC1230RYLGY250 12/3 WG MC Sol or/YI/Gy Alu ARMOR250' Southwire Company

Manufacturer Description Southwire Company Southwire Armorlite Type MC Cable Is Constructed With Soft-Drawn Copper Type THHN/THWN-2 Conductors Rated 90Å*C Dry and A Bare Copper Grounding Conductor For Sizes 1/0 Awg and Larger. The Conductors Are Cabled Together and A Binder Tape Bearing The Print Legend Is Wrapped Around The Assembly. Aluminum Interlocking Armor Is Applied Over The Assembly. Also Available In Steel. Conductors Are Black With Phase Identification. Colors Available Upon Request With Economic Order Quantity. Weight per unit O.1290 (lbs/each) Product Category Wire Features Conductor Size 12 media Yes Number of Conductors 3 outside diameter 0.50478 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Description Description 12/3 WG MC SOL OR/YL/GY ALU ARMOR250' extra long description 250 SwC 61127001 Armorlite Type MC Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90Å*C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are abled together and a binder tape bearing the print legend is wrapped around the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Southwire Company Catalog Number	MC1230RYLGY250		
Description Southwire Armorlite Type MC Cable Is Constructed With Soft-Drawn Copper Type THHN/THWN-2 Conductors Rated 90Å*C Dry and A Bare Copper Grounding Conductor For Sizes 1/0 Awg and Larger. The Conductors Are Cabled Together and A Binder Tape Bearing The Print Legend Is Wrapped Around The Assembly. Aluminum Interlocking Armor Is Applied Over The Assembly. Also Available In Steel. Conductors Are Black With Phase Identification. Colors Available Upon Request With Economic Order Quantity. Weight per unit 0.1290 (lbs/each) Product Category Wire Features Conductor Size 12 media Yes Number of Conductors 3 outside diameter 0.50478 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Description 12/3 WG MC SOL OR/YL/GY ALU ARMOR250' extra long description SWC 61127001 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90Å*C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Also available in steel. Conductors are lake with phase identification. Colors available upon request with economic order quantity.	<u> </u>			
Features Conductor Size Media Yes Number of Conductors Outside diameter Voltage Rating Outside Material Conductor Material CU Dimensions and Weight Length Description Description Outside Material Southwire Armorlite Type MC Armor Southwire Armorlite Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG available in steel. Conductors are plack with phase identification. Colors available upon request with economic order quantity.		Southwire Armorlite Type MC Cable Is Constructed With Soft-Drawn Copper Type THHN/THWN-2 Conductors Rated 90°C Dry and A Bare Copper Grounding Conductor For Sizes 1/0 Awg and Larger. The Conductors Are Cabled Together and A Binder Tape Bearing The Print Legend Is Wrapped Around The Assembly. Aluminum Interlocking Armor Is Applied Over The Assembly. Also Available In Steel. Conductors Are Black With Phase Identification. Colors Available Upon Request With Economic		
Features Conductor Size media Yes Number of Conductors 3 outside diameter 0.50478 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/3 WG MC SOL OR/YL/GY ALU ARMOR250' extra long description SWC 61127001 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper gounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Weight per unit	0.1290 (lbs/each)		
Conductor Size 12 media Yes Number of Conductors 3 outside diameter 0.50478 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/3 WG MC SOL OR/YL/GY ALU ARMOR250' extra long description SWC 61127001 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Product Category	Wire		
media Yes Number of Conductors 3 outside diameter 0.50478 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/3 WG MC SOL OR/YL/GY ALU ARMOR250' extra long description SWC 61127001 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Features			
Number of Conductors outside diameter Voltage Rating Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/3 WG MC SOL OR/YL/GY ALU ARMOR250' extra long description SWC 61127001 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Conductor Size	12		
outside diameter Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/3 WG MC SOL OR/YL/GY ALU ARMOR250' extra long description Swc 61127001 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.				
Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/3 WG MC SOL OR/YL/GY ALU ARMOR250' extra long description SWC 61127001 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.				
Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/3 WG MC SOL OR/YL/GY ALU ARMOR250' extra long description SWC 61127001 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.				
Conductor Material Dimensions and Weight Length 250 Descriptions Description 12/3 WG MC SOL OR/YL/GY ALU ARMOR250' extra long description SWC 61127001 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Voltage Rating	600V		
Descriptions Description Description Description Description Description Description Description Description SWC 61127001 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.		CU		
Description extra long description SWC 61127001 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	<u> </u>	250		
Description extra long description SWC 61127001 Armorlite Type MC Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Descriptions			
extra long description SWC 61127001 Armorlite Type MC Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.		12/3 WG MC SOL OR/YL/GY ALU ARMOR250'		
Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.		SWC 61127001 Armorlite Type MC		
Product Type Armorlite Type MC		soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification.		
	Product Type	Armorlite Type MC		



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

facturer	

Brand	Flexible Conduit
GTIN	00032886043994
Manufacturers Part Number	61127001
UPC	032886043994

Taxonomies, Classifications, and Categories

Category Description	BX & MC
Type	MC

Packaging

3 3	
Carton	250
Weight	32.215
Weight Per each	0.129