

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



MCT122SLBKWH250 MC 12/2 SL BK/WH/GN 250'

Catalog Number	MCT122SLBKWH250	
Manufacturer	Afc Cable	
Description	MC Cable, Stranded, 600 V, 250 FT Overall Length, Copper Conductor Material, Thermoplastic Insulation Material, Black, White and Green, 2 Conductors, +90 °C Operating Temperature, 0.147 LB/FT	
Weight per unit	0.1470 (lbs/each)	
Product Category	Teck	
Features		
Conductor Size	12 AWG Conductor And Ground	
outside diameter	0.495	
Voltage Rating	600	
Material, Color, and Finish		
Conductor Material	Copper	
Dimensions and Weight		
Length	250	
Descriptions		
Description	MC 12/2 SL BK/WH/GN 250'	
extra long description	KT 1704B42T00 12-2 MC TUFF 250' COI	
Special Features	Cable tray rated, install per NEC; May be surfaced mounted and embedded in plaster; Environmental air-handling space installation per NEC 300.22; UL Classi?ed 1, 2, and 3 hour through (Fire) penetration product, R-14141; Made in USA of US and/or imported materials; ColorSpec ID system	
Manufacturer Information		
Brand	AFC CABLE SYSTEMS	
GTIN	00077680195340	
sub brand	MC TUFF	
UPC	077680195340	
Taxonomies, Classifications, and	l Categories	
Category Description	BX & MC	

Taxo

rype I aditional Eightweight Type ivic capie with di	Dulla Alla Neuli al	
Type Traditional Lightweight Type MC Cable With Gr	round And Neutral	

Carton	250	
Weight	0.147	
Weight Per each	0.147	



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses,	Certifications,	and Standards
-------	-----------------	---------------

es, cei uncations, and standards	
standard	UL 83, 1479, 1569, 1581, 2556 File Number E80042, UL File
	Number R-14141, NEC 230.43, 300.22(C), 392, 396, 330, 501,
	502, 503, 530, 504, 505, 518, 520, 530, 645, Federal Speci?cation
	A-A-59544 (Formerly J-C-30B), Meets OSHA And HUD
	Requirements, ISO 9001 Certified
Temperature Rating	90 Deg C (Dry)