



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



NCMPDT10RJB Low Voltage Ceiling Mount Occupancy Sensor

Lithonia Lighting

Catalog Number	NCMPDT10RJB
Manufacturer	Lithonia Lighting
Description	The NCM PDT10 RJB Nlight Ceiling/Surface Mount Occupancy Sensors Provide A Range Of Networked Sensor Solutions For Applications With Finished Ceilings (E.G. Ceiling Tiles, Sheetrock, Plaster) Featuring Large Motion 360-Degree Coverage and 100% Digital Passive Infrared (Pir) Detection Combined With Microphonics to Detect Sound For Applications Where Occupants Are Stationary For Long Periods Of Time
Weight per unit	0.4000 (lbs/each)
Product Category	Lighting Occupancy Sensors

Features

Material	Plastic
Maximum Operating Temperature	60
pallet quantity	96
Voltage Rating	Low Voltage
Warranty	5

Material, Color, and Finish

Color	White
Finish	Gloss
Lens Material	Plastic

Dimensions and Weight

Height	4.5
Length	4.5
Width	2.5

Descriptions

Description	LOW VOLTAGE CEILING MOUNT OCCUPANCY SENSOR
extra long description	LITH NCM PDT 10 RJB Low Voltage Ce
Features	Design Select
Long Description	The nCM PDT10 RJB nLight ceiling/surface mount occupancy sensors provide a range of networked sensor solutions for applications with finished ceilings (e.g. ceiling tiles, sheetrock, plaster) featuring large motion 360-degree coverage and 100% digital Passive Infrared (PIR) detection combined with microphonics to detect sound for applications where occupants are stationary for long periods of time
Product Type	Sensor



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Manufacturer Information

Brand	Nlight
GTIN	00888791720754
Manufacturers Part Number	NCMPDT10RJB
UPC	888791720754

Taxonomies, Classifications, and Categories

Category Description	Commercial dimmers, motion sensors, & photo cells
Type	POWER PACK

Packaging

Carton	1
Weight	0.5
Weight Per each	0.4

Uses, Certifications, and Standards

Application	Automotive & Parking, Education, Government, Healthcare, Hospitality, House of Worship, Manufacturing, Offices & Banks, Power & Gas, Residential, Retail, Roadways, Bridges & Tunnels, Sports and Recreation, Transportation, Warehouses
environmental conditions	Indoor
Mounting	Flush, Surface
standard	C-UL-US, ULCA Title 24, DLC Standard, ROHS