

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

## NTC50 1/2" Rigid Threadless Raintight Connector Appleton/Oz Gedney

NTC50
Appleton/Oz Gedney
Compression Connector, Size: 1/2 In, Connection: Male Threaded X Compression, Material: Steel, Length: 1.26 In, Thread Length: 0.38 In, Diameter: 1.31 In, Standard: UI 514B, UI File Number E14814, Nema FB-1, For Use to Secure and Terminate Steel Emt to Knockouts and Concrete Tight Box
0.1500 (lbs/each)
Rigid Conduit Fittings - Steel
Male Threaded X Compression
Steel
1/2
1/2" RIGID THREADLESS RAINTIGHT CONNECTOR
APP NTC-50 1/2 IN CONN NO THRD RGD
Compression Connector, Size: 1/2 IN, Connection: Male Threaded X Compression, Material: Steel, Length: 1.26 IN, Thread Length: 0.38 IN, Diameter: 1.31 IN, Standard: UL 514B, UL File Number E14814, NEMA FB-1, For Use To Secure And Terminate Steel EMT To Knockouts And Concrete Tight Box
1/2 In Conn No THRD RGD Cond
Concretetight
Appleton
00781381637701
NTC-50
781381637701
Categories
Watertight Hub, 3-PIECE COUPLINGS, THREADLESS COUPLINGS AND THREADLESS CONNECTOR
Compression Connector
50
200

0.15

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	For Use To Secure And Terminate Steel EMT To Knockouts And
	Concrete Tight Box
standard	UL 514B, UL File Number E14814, NEMA FB-1