

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### PLG300 3" Recessed Plug Appleton/Oz Gedney

Catalog Number	PLG300
Manufacturer	Appleton/Oz Gedney
Description	Unilets Recessed Head Close-Up Plug, Size: 3 In, Material:
	Malleable Iron, Finish: Zinc Electroplate, Connection: Tapered
	MNPT, Standard: UI 886 (1203), UI File Number E10444, Csa
	C22.2 No. 25 and 30, Csa 065181, UI Listed For Class I, GR
Weight per unit	2.2 (lbs/each)
Product Category	Bar Hangers & Outlet Box Accy.
tures	

#### **Features**

connection	Tapered MNPT
Material	Malleable Iron

#### Material, Color, and Finish

Finish	Zinc Electroplate

#### **Dimensions and Weight**

Size	•	-
21/6		4
JILO		٠

#### **Descriptions**

3" RECESSED PLUG
APP PLG-300 PLUG 3 REC HEAD CLOSE-
UNILETS Recessed Head Close-Up Plug, Size: 3 IN, Material: Malleable Iron, Finish: Zinc Electroplate, Connection: Tapered MNPT, Standard: UL 886 (1203), UL File Number E10444, CSA C22.2 No. 25 And 30, CSA 065181, UL Listed For Class I, Gr
Plug 3 Rec Head Close-Up Iron
Accurately tapped, tapered threads for tight, rigid joints and ground continuity; Explosion proof, dust-ignition proof; Smooth, rounded integral bushing in each hub protects conductor insulation

#### **Manufacturer Information**

Brand	Appleton
GTIN	00781381652551
Manufacturers Part Number	PLG-300
UPC	781381652551

#### **Taxonomies, Classifications, and Categories**

Category Description	Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs,
	Knockout Plugs
Туре	Recessed Head Close-Up Plug



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Pac	kag	ıng
-----	-----	-----

Carton	5
Package	25
Weight Per each	2.16

#### Uses, Certifications, and Standards

Application	For Use With Threaded Rigid Metal Conduit and IMC
	· ·
standard	And Class III; Class II, Groups E, F, G; UL 886 (1203), UL File
	Number E10444, CSA C22.2 No. 25 And 30, CSA 065181, UL Listed
	For Class I, Groups B, C, D