

# Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

### PLT3SM 11.5" 50LB WHT CBL Tie Panduit Corporation

Catalag Number	
Catalog Number	PLT3SM Denduit Comparation
Manufacturer Description	Panduit Corporation Panduit PLT3S-M Locking Cable Ties Are Designed to Satisfy The Needs Of General Applications, While Delivering Consistent Performance and Reliability. Featuring A Curved Tip to Allow Fo Easy Pick Up From Flat Surfaces and Faster Initial Threading. Standard Cross Section, 11.5" (292MM) Length. For Indoor Use, Made Of Nylon 6.6, Are Natural In Color and Come In Packages Of 1000.
Weight per unit	0.0051 (lbs/each)
Product Category	Cable Ties & Wraps
eatures	
media	Yes
Tensile Strength	50
Dimensions and Weight	
Length	11.5
Thickness	0.06
escriptions	
Description	11.5" 50LB WHT CBL TIE
extra long description	PAN PLT3S-M Pan-Ty® PLT3S-M Cable T
Long Description	Panduit PLT3S-M Locking Cable Ties are designed to satisfy the needs of general applications, while delivering consistent performance and reliability. Featuring a curved tip to allow for easy pick up from flat surfaces and faster initial threading. Standard cross section, 11.5" (292mm) length. For indoor use, made of Nylon 6.6, are natural in color and come in packages of 1000.
Product Type	Pan-Ty® PLT3S-M Cable Tie, PA6.6, 11.5"L, 50LB, PK1000
Special Features	Indoor
Nanufacturer Information	
Brand	PANDUIT
GTIN	00074983540617
Manufacturers Part Number	PLT3S-M
UPC	074983540617
axonomies, Classifications, and (	Categories
Туре	Premium Cable Tie



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

### Packaging

Carton	1000
Package	2000
Weight Per each	0.005144

#### Uses, Certifications, and Standards

standard

CSA Certified, UL Recognized (File #E56854), UL 62275 Compliant (Type 2S, 21S), RoHS Compliant