

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Weight Per each

PRL1X3100X30A PRL1X Interior 208Y/120 3P 4W 100A 30 CKT AI Bus Eaton Corp

| p a Later corp | |
|------------------------------------|--|
| Catalog Number | PRL1X3100X30A |
| Manufacturer | Eaton Corp |
| Description | Eaton PRL1X Interior 120/208 3P 4W 100A 30 CKT AI Bus |
| Weight per unit | 102.0 (lbs/each) |
| Product Category | Distribution Equipment |
| Features | |
| amperage rating | 100A |
| dimensions | 43.7500 IN X 18.0000 IN X 6.2500 IN |
| media | Yes |
| Descriptions | |
| Description | PRL1X INTERIOR 208Y/120 3P 4W 100A 30 CKT AL BUS |
| extra long description | ETN PRL1X3100X30A PRL1X 208/120 3P4 |
| Features | The Pow-R-Xpress program brings to you a new set of products - |
| | Pow-R-Xpress panelboards. The Pow-R-Xpress products include |
| | interiors; type 1 and 3R boxes; surface and flush trims; main |
| | breaker kits; branch breakers; lug kits; service entrance kits; |
| | ground kits; and 200% neutral kits. In addition, the distributor |
| | stocking program can be used with various Eaton commercial |
| | distribution products and is designed to meet UL67 standards for |
| | use in data center, industrial, commercial and healthcare |
| | facilities. |
| Long Description | |
| Product Type | PRL1X 208/120 3P4W 100A 30 CKT AI Bus |
| Manufacturer Information | |
| Brand | Eaton |
| GTIN | 00786689363062 |
| Manufacturers Part Number | PRL1X3100X30A |
| UPC | 786689363062 |
| Taxonomies, Classifications, and G | Categories |
| Category Description | PANELBOARD BOXES & INTERIORS |
| Туре | PRL1X Panelboard |
| Packaging | |
| Carton | 1 |
| | |

102

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

| Application | Elec Assemblies, Panels & EOEM - Electrical Assemblies, Panels |
|-------------|--|
| | and EOEMs |
| standard | UL 67,NEMA Compliant |