

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

PSDS60AX 60A 600V SS N/F Safety Switch W/Aux

Catalog Number	PSDS60AX
Manufacturer	Pass & Seymour/Legrand
Description	60 Amps Stainless Steel Safety Switch With Auxiliary
	Contact.Legrands 316-Grade Stainless Steel Safety Switches Are
	Designed to Provide Superior Corrosion Resistance In Harsh
	Environments Like Food and Beverage Processing Plants Where
	Wash Down/Hose Down At Extreme Temperatures Is A Daily
	Necessity, As Well As Environments Where Salts, Acids, and Chemicals Are Prevalent. Legrands Stainless Steel Safety Switches
	With Nema 4X/12, IP66, 67, and 69K Ratings Are The Best
	Solution For Durability and Personnel Sa
Weight per unit	10.6 (lbs/each)
Product Category	Non-Fusible Heavy Duty Safety
Features	
Wire Size	#14 - #10 Awg
Descriptions	
Description	60A 600V SS N/F SAFETY SWITCH W/AUX
extra long description	P&S PSDS60AX 60A 600V SS NON-FUS SA
Long Description	60 Amps Stainless Steel Safety Switch with Auxiliary
	Contact.Legrands 316-Grade Stainless Steel Safety Switches are
	designed to provide superior corrosion resistance in harsh
	environments like food and beverage processing plants where
	wash down/hose down at extreme temperatures is a daily
	necessity, as well as environments where salts, acids, and chemicals are prevalent. Legrands Stainless Steel Safety Switches
	with NEMA 4X/12, IP66, 67, and 69K ratings are the best solution
	for durability and personnel sa
Product Type	60A 600V SS Non-Fus Safesw W/Ax
Manufacturer Information	
Brand	LEGRAND-PASS & SEYMOUR
GTIN	00785007133615
Manufacturers Part Number	PSDS60AX
UPC	785007133615
Taxonomies, Classifications, and C	
Category Description	Rotary Disconnects
Туре	Safety Switch
Trade Size	
Amperage	60.0



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging Carton	1
Weight Per each	10.6
Uses, Certifications, and Standards standard	cULus