

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Carton

Weight Per each

PVMA5LUNV1 48W, 120-277V Pvma Led, Mount Not Included *Crouse-Hinds*

Catalog Number	PVMA5LUNV1
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Champ Pro Pvma Led Light Fixture, Cool White, 150W MH, 50/60 HZ, Heat and Impact Resistant Glass Lens, 5000 Lumens, 122 LM/W, Die Cast Aluminum, No Mounting Module, Type V Optics, >0.90 PF, 48W
Weight per unit	13.2 (lbs/each)
Product Category	Lighting
eatures	
dimensions	10.1800 IN X 10.1800 IN X 7.1000 IN
escriptions	
Description	48W,120-277V PVMA LED,MOUNT NOT INCLUDED
extra long description	CRS-H PVMA5L/UNV1 LT LESS MOUNT 500
Features	Champ Pro PVMA low bay LED fixtures from Eaton's
	Crouse-Hinds Division are engineered to provide
	maintenance-free illumination in the most demanding
	environments. The Champ Pro PVMA features a compact, high efficacy design with custom Type V optics to ensure maximum efficiency and mounting flexibility, including the ability to retrofi the Crouse-Hinds installed base to service both LED upgrades an new projects. The compact and lightweight PVMA LED is available in 5,000 and 7,500 lumen models. It is de
Long Description	Eaton Crouse-Hinds series Champ Pro PVMA LED light fixture, Cool white, 150W MH, 50/60 Hz, Heat and impact resistant glass lens, 5000 lumens, 122 lm/W, Die cast aluminum, No mounting module, Type V optics, >0.90 PF, 48W
Product Type	LT Less Mount 5000 Lumen
Nanufacturer Information	
Brand	Eaton
GTIN	00662276826236
Manufacturers Part Number	PVMA5L/UNV1
UPC	662276826236
axonomies, Classifications, and (Categories
	LED HIGHBAY, LOWBAY & INDUSTRIAL LIGHTING
Туре	
ackaging	
Corton	1

13.2

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Lighting and Lighting Controls
standard	IFFX.E502234