

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## **RE42SA 1-1/4X3/4 Alu Reducing Bushing** Crouse-Hinds

Catalog Number	
Catalog Number Manufacturer	RE42SA Crouse-Hinds
Description	Eaton Crouse-Hinds Series Re Reducer, Rigid/Imc, End 1: 1-1/4"
Description	NPT, End 2: 3/4" NPT, Copper-Free Aluminum
Weight per unit	
Product Category	
0	Adminum
Features	
connection	
dimensions	
Material	Copper-Free Aluminum
Descriptions	
Description	1-1/4X3/4 ALU REDUCING BUSHING
extra long description	CRS-H RE42 SA 1 1/4 TO 3/4 AL REDUC
Features	Crouse-Hinds series RE, REA and REC explosionproof reducers are
	used in rigid/IMC conduit systems to reduce conduit hubs to a
	smaller size (RE), connect two different sizes of conduit together
	(REC), or enlarge drilled and tapped openings by one NPT size
	(REA). PLG explosionproof plugs are used for closing threaded
	conduit hubs.
Long Description	Eaton Crouse-Hinds series RE reducer, Rigid/IMC, End 1: 1-1/4"
	NPT, End 2: 3/4" NPT, Copper-free aluminum
Product Type	1 1/4 to 3/4 Al Reducing Bush
Special Features	Reducing fitting
Manufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274101439
Manufacturers Part Number	RE42 SA
UPC	782274101439
Taxonomies, Classifications, and	Categories
Category Description	Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs,

Category Description	Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs,
	Knockout Pluas
Туре	REDUCER
Packaging	
Carton	10
Weight Per each	0.14



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group A B C D, Class II Div 1 Group E F G, Class II
	Div 2 Group F G, Class III
standard	UL 886, CSA C22.2