

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



# **RE43SA 1-1/4X1 Alu Reducing Bushing** *Crouse-Hinds*

Catalog Number	RE43SA
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Re Reducer, Rigid/Imc, End 1: 1-1/4" NPT, End 2: 1" NPT, Copper-Free Aluminum
Weight per unit	
Product Category	Aluminum
atures	

#### Fea

connection	Threaded
dimensions	1.6600 IN X 1.0600 IN X 1.6600 IN
Material	Copper-Free Aluminum

1-1/4X1 ALU REDUCING BUSHING

### **Descriptions**

Description

extra long description	CRS-H RE43 SA 1 1/4 TO 1 AL REDUCIN
extra long description Features	Crouse-Hinds series RE, REA and REC explosionproof reducers are used in rigid/IMC conduit systems to reduce conduit hubs to a smaller size (RE), connect two different sizes of conduit together (REC), or enlarge drilled and tapped openings by one NPT size (REA). PLG explosionproof plugs are used for closing threaded conduit hubs.
Long Description	Eaton Crouse-Hinds series RE reducer, Rigid/IMC, End 1: 1-1/4" NPT, End 2: 1" NPT, Copper-free aluminum
Product Type	1 1/4 to 1 Al Reducing Bush
Special Features	Reducing fitting

#### **Manufacturer Information**

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274101446
Manufacturers Part Number	RE43 SA
UPC	782274101446

## **Taxonomies, Classifications, and Categories**

Category Description	Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs,
	Knockout Plugs
Type	REDUCER

### **Packaging**

Carton	1	
Package	10	
Weight Per each	0.08	

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

### **Uses, Certifications, and Standards**

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group A B C D, Class II Div 1 Group E F G, Class II
	Div 2 Group F G, Class III
standard	UL 886, CSA C22.2