



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



RE62 2X3/4 Reducing Bushing

Crouse-Hinds

| | |
|------------------|--|
| Catalog Number | RE62 |
| Manufacturer | Crouse-Hinds |
| Description | Reducing Bushing, 2 to 3/4 In Trade Size, Re Model, Electro Galvanized and Aluminum Acrylic Paint, 2.375 In Length, 0.85 LB/Ea |
| Weight per unit | 0.8500 (lbs/each) |
| Product Category | Rigid Conduit Fittings - Steel |

Features

| | |
|------------|-----------------------------------|
| connection | Threaded |
| dimensions | 2.3800 IN X 1.0000 IN X 2.3800 IN |
| Material | Copper Free Aluminum |

Material, Color, and Finish

| | |
|--------|---|
| Finish | Electrogalvanized With Aluminum Acrylic Painted |
|--------|---|

Dimensions and Weight

| | |
|------|-------------|
| Size | 2 To 3/4 In |
|------|-------------|

Descriptions

| | |
|------------------------|--|
| Description | 2X3/4 REDUCING BUSHING |
| extra long description | CRS-H RE62 2 TO 3/4 REDUCING BUSH |
| Features | Crouse-Hinds series RE, REA and REC explosionproof reducers are used in rigid/IMC conduit systems to reduce conduit hubs to a smaller size (RE), connect two different sizes of conduit together (REC), or enlarge drilled and tapped openings by one NPT size (REA). PLG explosionproof plugs are used for closing threaded conduit hubs. |

Manufacturer Information

| | |
|-------|----------------|
| Brand | Eaton |
| GTIN | 00782274590608 |
| UPC | 782274590608 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|---|
| Category Description | Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs, Knockout Plugs |
| Type | REDUCER |

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Package | 10 |
| Weight Per each | 0.85 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Enclosure

Class I Div 1 2 Group A B C D, Class II Div 1 Group E F G, Class II
Div 2 Group F G, Class III

standard

UL 886, CSA C22.2