



**Atlanta, Georgia**

**Phone 800-521-7326**

**Fax 770-745-1333**

## **Roof Jack - Lead Free Aluminum Base - Black**



<b>Peco Catalog#</b>	<b>Top Opening</b>	<b>Pipe Range</b>	<b>Base Size Length</b>	<b>Base Size Width</b>	<b>ASTM Requirement</b>	<b>Material</b>
RS051BA	Closed	Closed thru 3-1/4"	16 In.	19-1/4 in.	C20	EPDM*

Can be used with Type B vents due to added Fire Retardant IAPMO Cert No. 3121

\*Ethylene Propylene Diene Terpolymer - Black

Built-In 20% pitch allows adaptability to almost any roof pitch including 45 degree

Pull tab design and easy smooth tear grooving is intended to eliminate razor knives

Marked with dimensions to allow for easy sizing to fit each individual application.

Aluminum panel allows the pipe boot flashing to conform to any panel configuration and/or roof pitch

Peco Fasteners specification sheets are a reference guide to help in the selection of fasteners. Peco has made every effort to ensure the accuracy of the information. However, Peco Fasteners is not responsible for any errors that may be contained within these sheets. Peco Fasteners makes no claim of warranty in the accuracy of this information. Users of this information are solely responsible for protecting themselves against liability. It is solely the responsibility of the purchasers and users of these fasteners to consult with Engineers that are experts in an applicable field. Peco Fasteners is not responsible for any loss, claim, or damage due to these specification sheets.

4/13/22



**Atlanta, Georgia**

**Phone 800-521-7326**

**Fax 770-745-1333**

## **Roof Jack - Lead Free Aluminum Base - Black**



<b>Peco Catalog#</b>	<b>Top Opening</b>	<b>Pipe Range</b>	<b>Base Size Length</b>	<b>Base Size Width</b>	<b>ASTM Requirement</b>	<b>Material</b>
RS051BA	Closed	Closed thru 3-1/4"	16 In.	19-1/4 in.	C20	EPDM*

Can be used with Type B vents due to added Fire Retardant IAPMO Cert No. 3121

\*Ethylene Propylene Diene Terpolymer - Black

Built-In 20% pitch allows adaptability to almost any roof pitch including 45 degree

Pull tab design and easy smooth tear grooving is intended to eliminate razor knives

Marked with dimensions to allow for easy sizing to fit each individual application.

Aluminum panel allows the pipe boot flashing to conform to any panel configuration and/or roof pitch

Peco Fasteners specification sheets are a reference guide to help in the selection of fasteners. Peco has made every effort to ensure the accuracy of the information. However, Peco Fasteners is not responsible for any errors that may be contained within these sheets. Peco Fasteners makes no claim of warranty in the accuracy of this information. Users of this information are solely responsible for protecting themselves against liability. It is solely the responsibility of the purchasers and users of these fasteners to consult with Engineers that are experts in an applicable field. Peco Fasteners is not responsible for any loss, claim, or damage due to these specification sheets.

4/13/22