



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



RSLB216H Hygienic LB 3/4"

Robroy/Stainless Steel

Catalog Number	RSLB216H
Manufacturer	Robroy/Stainless Steel
Description	Robroy Stainless Hygienic Conduit Bodies Are Designed to Withstand Harsh Corrosive Environments. Conduit Bodies Are 316 Stainless Steel and Are Used to Change The Direction Of Conduit and Make Wiring Pulls and Connections. Hygienic Conduit Bodies Come With A Cast Stainless Cover, A Fda Approved Silicone Gasket and Sure Stop Hex Screws. All Female Threads Include A Fda Approved Silicone Circular Gasket.
Weight per unit	2.3 (lbs/each)
Product Category	Boxes & Covers

Features

Overall Height	4.03
Overall Width	1.76

Material, Color, and Finish

Finish	Electro-polished
--------	------------------

Dimensions and Weight

Overall Length	6.4
----------------	-----

Descriptions

Description	HYGIENIC LB 3/4"
extra long description	ROB-R LB216H LB HYG COND Body 3/4"
Long Description	Robroy Stainless Hygienic Conduit Bodies are designed to withstand harsh corrosive environments. Conduit bodies are 316 stainless steel and are used to change the direction of conduit and make wiring pulls and connections. Hygienic conduit bodies come with a cast stainless cover, a FDA approved silicone gasket and sure stop hex screws. All female threads include a FDA approved silicone circular gasket.
Product Type	LB Hyg Cond Body 3/4" 316 W/Cond Ent GSKT

Manufacturer Information

Brand	Robroy Stainless
GTIN	00784011919499
Manufacturers Part Number	LB216H
UPC	784011919499

Taxonomies, Classifications, and Categories

Type	Conduit Body Assemblies
------	-------------------------

Trade Size

Trade Size	3/4
------------	-----



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton	1
Weight	2.33
Weight Per each	2.33

Uses, Certifications, and Standards

standard	UL 514B, E231035, CSA C22.2 No. 18.1-04, NSF/ANSI/3-A 14159-1, TYPE 4X,IP69/IP69K
----------	--