## SATCO' NUVO

Project Name

Prepared By



## **SATCO S29837** 9.8A19/OMNI/220/LED/35K

Notes

StatusActiveWatts9.8WIncandescent Equivalent60WVolts120VShapeA19BaseMediumANSI BaseE26FinishFrostCCT (kelvin)3500KTemperatureNeutral WhiteCRI80-4Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnology60HzOperating Frequency60HzOperating Temperature.25C (-13F) to +45C (+113F)Physical.362MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.06Additional InformationYesWarranty5-Years
Incandescent Equivalent60WVolts120VShapeA19BaseMediumANSI BaseE26FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnology60HzOperating Frequency60HzOperating Temperature0.98Operating Temperature0.98Operating Temperature3562MOL4.331MOL3.362Housing ColorWhiteWeight (Ib.)0.06Additional InformationYes
Volts120VShapeA19BaseMediumANSI BaseE26FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating ColorWhiteMOL4.331MOD2.362Housing ColorWhiteWeight (Ib.)0.06Rated For Enclosed FixtureYes
ShapeA19BaseMediumANSI BaseE26FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyEEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature4.331MOL4.331MOD2.362Housing ColorWhiteWeight (Ib.)0.06Additional InformationYes
BaseMediumBaseMediumANSI BaseE26FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.06Additional InformationYes
ANSI BaseE26FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnology60HzOperating Frequency60HzOperating Temperature0.98Operating Color331MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.06Rated For Enclosed FixtureYes
FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyEEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical
CCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Color4.331MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.06Rated For Enclosed FixtureYes
TemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical
CRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical
Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical311MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.06Rated For Enclosed FixtureYes
Beam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical
DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical
Hours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical311MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.06Additional InformationYes
Product CategoryType ATechnologyLEDElectrical0Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical4.331MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.06Additional InformationYes
TechnologyLEDElectricalOperating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.06Additional InformationYes
Electrical         Operating Frequency       60Hz         Power Factor       0.98         Operating Temperature       -25C (-13F) to +45C (+113F)         Physical       4.331         MOL       4.331         MOD       2.362         Housing Color       White         Weight (lb.)       0.06         Additional Information       Yes
Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical
Power Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical
Power Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical
Operating Temperature     -25C (-13F) to +45C (+113F)       Physical       MOL     4.331       MOD     2.362       Housing Color     White       Weight (lb.)     0.06       Additional Information       Rated For Enclosed Fixture     Yes
MOL     4.331       MOD     2.362       Housing Color     White       Weight (Ib.)     0.06       Additional Information       Rated For Enclosed Fixture     Yes
MOL     4.331       MOD     2.362       Housing Color     White       Weight (Ib.)     0.06       Additional Information       Rated For Enclosed Fixture     Yes
MOD     2.362       Housing Color     White       Weight (Ib.)     0.06       Additional Information       Rated For Enclosed Fixture     Yes
Housing Color     White       Weight (lb.)     0.06       Additional Information     Rated For Enclosed Fixture
Weight (Ib.)     0.06       Additional Information     Rated For Enclosed Fixture       Yes     Yes
Additional Information Rated For Enclosed Fixture Yes
Rated For Enclosed Fixture Yes
Warranty 5-Years
Compliance
Safety Listing cULus - Certified; cULus - Listed
Location Rating Damp
California Status Non-Compliant
Title 20 / 24 Status Non-Compliant
Colorado Status Lawful for sale
Hawaii Status Lawful for sale
Novada Status
Nevada Status Lawful for sale
Vermont Status Lawful for sale
Vermont Status Lawful for sale
Vermont Status     Lawful for sale       Washington Status     Lawful for sale

## SATCO' NUVO

Project Name

Prepared By



## **SATCO S29837** 9.8A19/OMNI/220/LED/35K

Notes

StatusActiveWatts9.8WIncandescent Equivalent60WVolts120VShapeA19BaseMediumANSI BaseE26FinishFrostCCT (kelvin)3500KTemperatureNeutral WhiteCRI80-4Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnology60HzOperating Frequency60HzOperating Temperature.25C (-13F) to +45C (+113F)Physical.362MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.06Additional InformationYesWarranty5-Years
Incandescent Equivalent60WVolts120VShapeA19BaseMediumANSI BaseE26FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnology60HzOperating Frequency60HzOperating Temperature0.98Operating Temperature0.98Operating Temperature3562MOL4.331MOL3.362Housing ColorWhiteWeight (Ib.)0.06Additional InformationYes
Volts120VShapeA19BaseMediumANSI BaseE26FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating ColorWhiteMOL4.331MOD2.362Housing ColorWhiteWeight (Ib.)0.06Rated For Enclosed FixtureYes
ShapeA19BaseMediumANSI BaseE26FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyEEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature4.331MOL4.331MOD2.362Housing ColorWhiteWeight (Ib.)0.06Additional InformationYes
BaseMediumBaseMediumANSI BaseE26FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.06Additional InformationYes
ANSI BaseE26FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnology60HzOperating Frequency60HzOperating Temperature0.98Operating Color331MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.06Rated For Enclosed FixtureYes
FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyEEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical
CCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Color4.331MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.06Rated For Enclosed FixtureYes
TemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical
CRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical
Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical311MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.06Rated For Enclosed FixtureYes
Beam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical
DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical
Hours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical311MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.06Additional InformationYes
Product CategoryType ATechnologyLEDElectrical0Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical4.331MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.06Additional InformationYes
TechnologyLEDElectricalOperating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.06Additional InformationYes
Electrical         Operating Frequency       60Hz         Power Factor       0.98         Operating Temperature       -25C (-13F) to +45C (+113F)         Physical       4.331         MOL       4.331         MOD       2.362         Housing Color       White         Weight (lb.)       0.06         Additional Information       Yes
Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical
Power Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical
Power Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical
Operating Temperature     -25C (-13F) to +45C (+113F)       Physical       MOL     4.331       MOD     2.362       Housing Color     White       Weight (lb.)     0.06       Additional Information       Rated For Enclosed Fixture     Yes
MOL     4.331       MOD     2.362       Housing Color     White       Weight (Ib.)     0.06       Additional Information       Rated For Enclosed Fixture     Yes
MOL     4.331       MOD     2.362       Housing Color     White       Weight (Ib.)     0.06       Additional Information       Rated For Enclosed Fixture     Yes
MOD     2.362       Housing Color     White       Weight (Ib.)     0.06       Additional Information       Rated For Enclosed Fixture     Yes
Housing Color     White       Weight (Ib.)     0.06       Additional Information     Rated For Enclosed Fixture
Weight (Ib.)     0.06       Additional Information     Rated For Enclosed Fixture       Yes     Yes
Additional Information Rated For Enclosed Fixture Yes
Rated For Enclosed Fixture Yes
Warranty 5-Years
Compliance
Safety Listing cULus - Certified; cULus - Listed
Location Rating Damp
California Status Non-Compliant
Title 20 / 24 Status Non-Compliant
Colorado Status Lawful for sale
Hawaii Status Lawful for sale
Novada Status
Nevada Status Lawful for sale
Vermont Status Lawful for sale
Vermont Status Lawful for sale
Vermont Status     Lawful for sale       Washington Status     Lawful for sale