## SATCO NUVO

Project Name

\_\_\_\_

Location Prepared By



9.8A19/OMNI/220/LED/35K/GU24

Notes

StatusActiveWatts9.8WIncandescent Equivalent60WVolts120VShapeA19BaseBi Pin GU24ANSI BaseGU24FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical-25C (-13F) to +45C (+113F)Operating Temperature0.98Operating Temperature0.97MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Additional InformationYesWarranty5-Years
Incandescent Equivalent60WVolts120VShapeA19BaseBi Pin GU24ANSI BaseGU24FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DinmableYes-DinmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOLMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Additional InformationYesRated For Enclosed FixtureYes
Volts120VShapeA19BaseBi Pin GU24ANSI BaseGU24FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOLMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Rated For Enclosed FixtureYes
ShapeA19BaseBi Pin GU24ANSI BaseGU24FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOLMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Rated For Enclosed FixtureYes
BaseBi Pin GU24ANSI BaseGU24FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectricalOperating Frequency60HzOperating Temperature0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Rated For Enclosed FixtureYes
ANSI BaseGU24FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnology60HzOperating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Rated For Enclosed FixtureYes
FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalIMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Rated For Enclosed FixtureYes
CCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical1.331MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Rated For Enclosed FixtureYes
TemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical
CRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectricalOperating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Rated For Enclosed FixtureYes
LumensBOOLBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical
Beam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectricalOperating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Additional InformationRated For Enclosed FixtureYes
DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectricalOperating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Rated For Enclosed FixtureYes
Hours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical311MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Rated For Enclosed FixtureYes
Product CategoryType ATechnologyLEDElectricalOperating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Additional InformationYes
TechnologyLEDElectricalOperating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Additional InformationYes
Electrical   Operating Frequency 60Hz   Power Factor 0.98   Operating Temperature -25C (-13F) to +45C (+113F)   Physical 4.331   MOL 4.331   MOD 2.362   Housing Color White   Weight (lb.) 0.07   Additional Information Yes
Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical4.331MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Additional InformationYesRated For Enclosed FixtureYes
Power Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Additional InformationYes
Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Additional InformationYes
Physical   MOL 4.331   MOD 2.362   Housing Color White   Weight (lb.) 0.07   Additional Information   Rated For Enclosed Fixture Yes
MOL 4.331   MOD 2.362   Housing Color White   Weight (lb.) 0.07   Additional Information   Rated For Enclosed Fixture Yes
MOD 2.362   Housing Color White   Weight (lb.) 0.07   Additional Information   Rated For Enclosed Fixture Yes
Housing Color White   Weight (lb.) 0.07   Additional Information Rated For Enclosed Fixture
Weight (lb.) 0.07   Additional Information Rated For Enclosed Fixture
Weight (lb.) 0.07   Additional Information Rated For Enclosed Fixture
Rated For Enclosed Fixture Yes
Rated For Enclosed Fixture Yes
Compliance
Safety Listing CULus - Certified; cULus - Listed
Location Rating Damp
California Status Non-Compliant
Title 20 / 24 Status Non-Compliant
Colorado Status Lawful for sale
Hawaii Status Lawful for sale
Nevada Status Lawful for sale
Vermont Status Lawful for sale
Washington Status Lawful for sale
RoHS Compliant Yes
FCC Compliant Yes

## SATCO NUVO

Project Name

\_\_\_\_

Location Prepared By



9.8A19/OMNI/220/LED/35K/GU24

Notes

StatusActiveWatts9.8WIncandescent Equivalent60WVolts120VShapeA19BaseBi Pin GU24ANSI BaseGU24FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical-25C (-13F) to +45C (+113F)Operating Temperature0.98Operating Temperature0.97MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Additional InformationYesWarranty5-Years
Incandescent Equivalent60WVolts120VShapeA19BaseBi Pin GU24ANSI BaseGU24FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DinmableYes-DinmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOLMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Additional InformationYesRated For Enclosed FixtureYes
Volts120VShapeA19BaseBi Pin GU24ANSI BaseGU24FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOLMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Rated For Enclosed FixtureYes
ShapeA19BaseBi Pin GU24ANSI BaseGU24FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOLMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Rated For Enclosed FixtureYes
BaseBi Pin GU24ANSI BaseGU24FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectricalOperating Frequency60HzOperating Temperature0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Rated For Enclosed FixtureYes
ANSI BaseGU24FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnology60HzOperating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Rated For Enclosed FixtureYes
FinishFrostCCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalIMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Rated For Enclosed FixtureYes
CCT (Kelvin)3500KTemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical1.331MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Rated For Enclosed FixtureYes
TemperatureNeutral WhiteCRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical
CRI80+Lumens800LBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectricalOperating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Rated For Enclosed FixtureYes
LumensBOOLBeam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical
Beam Spread220DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectricalOperating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Additional InformationRated For Enclosed FixtureYes
DimmableYes-DimmableHours Rated25000Product CategoryType ATechnologyLEDElectricalOperating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Rated For Enclosed FixtureYes
Hours Rated25000Product CategoryType ATechnologyLEDElectrical0.98Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical311MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Rated For Enclosed FixtureYes
Product CategoryType ATechnologyLEDElectricalOperating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Additional InformationYes
TechnologyLEDElectricalOperating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Additional InformationYes
Electrical   Operating Frequency 60Hz   Power Factor 0.98   Operating Temperature -25C (-13F) to +45C (+113F)   Physical 4.331   MOL 4.331   MOD 2.362   Housing Color White   Weight (lb.) 0.07   Additional Information Yes
Operating Frequency60HzPower Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)Physical4.331MOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Additional InformationYesRated For Enclosed FixtureYes
Power Factor0.98Operating Temperature-25C (-13F) to +45C (+113F)PhysicalMOL4.331MOD2.362Housing ColorWhiteWeight (lb.)0.07Additional InformationYes
Operating Temperature -25C (-13F) to +45C (+113F)   Physical   MOL 4.331   MOD 2.362   Housing Color White   Weight (lb.) 0.07   Additional Information   Rated For Enclosed Fixture Yes
Physical   MOL 4.331   MOD 2.362   Housing Color White   Weight (lb.) 0.07   Additional Information   Rated For Enclosed Fixture Yes
MOL 4.331   MOD 2.362   Housing Color White   Weight (lb.) 0.07   Additional Information   Rated For Enclosed Fixture Yes
MOD 2.362   Housing Color White   Weight (lb.) 0.07   Additional Information   Rated For Enclosed Fixture Yes
Housing Color White   Weight (lb.) 0.07   Additional Information Rated For Enclosed Fixture
Weight (lb.) 0.07   Additional Information Rated For Enclosed Fixture
Weight (lb.) 0.07   Additional Information Rated For Enclosed Fixture
Rated For Enclosed Fixture Yes
Rated For Enclosed Fixture Yes
Compliance
Safety Listing CULus - Certified; cULus - Listed
Location Rating Damp
California Status Non-Compliant
Title 20 / 24 Status Non-Compliant
Colorado Status Lawful for sale
Hawaii Status Lawful for sale
Nevada Status Lawful for sale
Vermont Status Lawful for sale
Washington Status Lawful for sale
RoHS Compliant Yes
FCC Compliant Yes