



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



SB387NM 2-1/2" Non-Metallic Split Bushing *Bridgeport Fittings*

| | |
|------------------|--|
| Catalog Number | SB387NM |
| Manufacturer | Bridgeport Fittings |
| Description | Split Bushing, Insulated, Plastic, 2.5 Inch Trade Size. Patented |
| Weight per unit | 0.0520 (lbs/each) |
| Product Category | Plastic |

Features

| | |
|----------|---------------|
| Material | Nylon Plastic |
| media | Yes |

Material, Color, and Finish

| | |
|--------|-----------|
| Color | Gray |
| Finish | NO FINISH |

Dimensions and Weight

| | |
|------|-------|
| Size | 2-1/2 |
|------|-------|

Descriptions

| | |
|------------------------|--|
| Description | 2-1/2" NON-METALLIC SPLIT BUSHING |
| extra long description | BPT SB-387NM 2-1/2" NON-METALLIC SP |
| Features | Split Bushings install after the wire pull. No more burning through bushings or fighting with pullers. Save time and effort too! |
| Long Description | Split Bushing, Insulated, Plastic, 2.5 Inch Trade Size. Patented |
| Product Type | 2-1/2" Non-Metallic Split Bush |

Manufacturer Information

| | |
|---------------------------|---------------------|
| Brand | Bridgeport Fittings |
| GTIN | 00781747403872 |
| Manufacturers Part Number | SB-387NM |
| UPC | 781747403872 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|---|
| Category Description | COUPLINGS, ADAPTERS, REDUCERS, BUSHINGS, & CAPS |
| Type | BUSHING |

Trade Size

| | |
|------------|-----|
| Trade Size | 2.5 |
|------------|-----|

Packaging

| | |
|-----------------|-------|
| Carton | 25 |
| Weight Per each | 0.052 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application

Used in situations where wires have already been pulled through Rigid/IMC conduit, and an insulated bushing is required. Rated 105 Degree C. cULus listed. Patented

standard

cULus

Temperature Rating

105 Degree C