SL35911 -- Nickel Anti-Seize Lubricating Compound, 8 Wt Oz



Product Description

Sta-Lube Nickel Anti-Seize is a nickel based formula that is free of copper, lead, sulfides and chlorides. This premium quality lubricant has extremely high temperature and excellent chemical resistance.

Product Specifications Applications

Unit Package Description Brand **Generic Description 1** Net Fill UPC Code **Unit Dimensions-Inches** Units Per Case **Case Dimensions-Inches** Cases Per Pallet Lbs. Per Case I 2 of 5 Code Appearance Odor Base Type Flashpoint - TCC Method Specific Gravity Flammability **Plastic Safe** Film Type **Evaporation Rate** Working Temp [Degrees F] Propellant **NSF Registered** DOT Proper Shipping Name VOC % (Federal) VOC g/L (Federal) VOC Lbs./Gal. (Federal) **VOC Compliant For CA VOC Compliant For OTC/** LADCO VOC Category/Limit Removal (How To)

Catalyst beds, reaction chambers, special alloy fittings. May be used on fittings, bushings, flanges, headers, nuts, screws, studs, threaded surfaces, pipes, plugs, and manifolds to prevent seizing and galling of surfaces. 8 Ounce Brush-Top Bottle Sta-Lube General Purpose Anti Seize Lubricant 8 Wt Oz 0 72213 35911 4 4.25H x 2.5W x 2.5D 12 5H x 6.63W x 10D 108 8 30072213359115 Silver Semi-Solid Paste Petroleum Nickel 430°F 1.24 Non-flammable Yes Wet <0.01 (Butyl Acetate=1) -95 to 2400°F None No Not Regulated 0 0 0 Not Regulated Not Regulated Not Regulated Remove with general purpose degreaser.

SL35911 -- Nickel Anti-Seize Lubricating Compound, 8 Wt Oz



Product Description

Sta-Lube Nickel Anti-Seize is a nickel based formula that is free of copper, lead, sulfides and chlorides. This premium quality lubricant has extremely high temperature and excellent chemical resistance.

Product Specifications Applications

Unit Package Description Brand **Generic Description 1** Net Fill UPC Code **Unit Dimensions-Inches** Units Per Case **Case Dimensions-Inches** Cases Per Pallet Lbs. Per Case I 2 of 5 Code Appearance Odor Base Type Flashpoint - TCC Method Specific Gravity Flammability **Plastic Safe** Film Type **Evaporation Rate** Working Temp [Degrees F] Propellant **NSF Registered** DOT Proper Shipping Name VOC % (Federal) VOC g/L (Federal) VOC Lbs./Gal. (Federal) **VOC Compliant For CA VOC Compliant For OTC/** LADCO VOC Category/Limit Removal (How To)

Catalyst beds, reaction chambers, special alloy fittings. May be used on fittings, bushings, flanges, headers, nuts, screws, studs, threaded surfaces, pipes, plugs, and manifolds to prevent seizing and galling of surfaces. 8 Ounce Brush-Top Bottle Sta-Lube General Purpose Anti Seize Lubricant 8 Wt Oz 0 72213 35911 4 4.25H x 2.5W x 2.5D 12 5H x 6.63W x 10D 108 8 30072213359115 Silver Semi-Solid Paste Petroleum Nickel 430°F 1.24 Non-flammable Yes Wet <0.01 (Butyl Acetate=1) -95 to 2400°F None No Not Regulated 0 0 0 Not Regulated Not Regulated Not Regulated Remove with general purpose degreaser.