




SR TRACE®

SELF-REGULATING, PRE-TERMINATED CABLE



SR Trace® is a self-regulating heating cable that automatically varies its heat output with changes in surrounding temperature. Normally installed in commercial applications, SR Trace helps provide maximum freeze protection for pipes and vessels in ambient temperatures down to -40°F/-40°C. Use SR Trace cables to prevent water pipes from freezing, to maintain liquids in pipes at a constant temperature in order to prevent degradation of the liquid, or to maintain viscosity for flow conditions. SR Trace can be installed in dry or wet environments. Available in power densities of 3, 5, and 8 watts per foot at 50°F/10°C, for both 120 Vac and 240 Vac applications. 240 Vac can be used for 208 Vac or 277 Vac applications. SR Trace cables are UL Listed to US and Canadian Safety Standards and CSA Certified. See item specific certifications below.

CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
SR31CB	3 w/ft, 120 Vac, cut-to-order	-	-	-	
JP31CB	3 w/ft, 120 Vac Job Pack (100' cable, 2-SRP,1-SRST,1-SRTCS)	1	8	0-13627-06931-2	
SR32CB	3 w/ft, 240 Vac, cut-to-order	-	-	-	
JP32CB	3 w/ft, 240 Vac Job Pack (100' cable, 2-SRP,1-SRST,1-SRTCS)	1	8	0-13627-06932-9	
SR51CB	5 w/ft, 120 Vac, cut-to-order	-	-	-	
JP51CB	5 w/ft, 120 Vac Job Pack (100' cable, 2-SRP,1-SRST,1-SRTCS)	1	8	0-13627-06930-5	
SR52CB	5 w/ft, 240 Vac, cut-to-order	-	-	-	
JP52CB	5 w/ft, 240 Vac Job Pack (100' cable, 2-SRP,1-SRST,1-SRTCS)	1	8	0-13627-06929-9	
SR81CB	8 w/ft, 120 Vac, cut-to-order	-	-	-	
SR82CB	8 w/ft, 240 Vac, cut-to-order	-	-	-	
SR31J	3 w/ft, 120 Vac, cut-to-order	-	-	-	
SR31J250	250' self-dispensing reel	1	20	0-13627-06925-1	
SR32J	3 w/ft, 240 Vac, cut-to-order	-	-	-	
SR32J250	250' self-dispensing reel	1	20	0-13627-06923-7	
SR51J	5 w/ft, 120 Vac, cut-to-order	-	-	-	
SR51J250	SR51J on a 250' Reel	1	20	0-13627-06921-3	
SR51J750	750' self-dispensing reel	1	72	0-13627-06922-0	
JP51J	5 w/ft, 120 Vac Job Pack (100' cable, 2-SRP,1-SRST,1-SRTCS)	1	8	0-13627-06927-5	
SR52J	5 w/ft, 240 Vac, cut-to-order	-	-	-	
SR52J250	SR52J on a 250' Reel	1	20	0-13627-06919-0	
SR52J750	750' self-dispensing reel	1	72	0-13627-06920-6	
JP52J	5 w/ft, 240 Vac Job Pack (100' cable, 2-SRP,1-SRST,1-SRTCS)	1	8	0-13627-06928-2	
SR81J	8 w/ft, 120 Vac, cut-to-order	-	-	-	
SR81J250	250' self-dispensing reel	1	20	0-13627-06917-6	
SR82J	8 w/ft, 240 Vac, cut-to-order	-	-	-	
SR82J250	250' self-dispensing reel	1	20	0-13627-06815-2	

SR TRACE ACCESSORIES

Specially designed kits ease installation and connection of SR Trace products. SR Trace accessories are UL Listed and CSA Certified.



CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
SRP	Heat shrink power/end connection kit	1	3	0-13627-06947-3	 
SRST	Heat shrink splice and "T" connection kit	2	2	0-13627-06959-6	
SRES	Heat shrink end seal kit	5	2	0-13627-06968-8	
SRTCS	Fiberglass application tape and caution signs	1	2	0-13627-06970-1	

SR TRACE®

SELF-REGULATING, PRE-TERMINATED CABLE



SR Trace® is a self-regulating heating cable that automatically varies its heat output with changes in surrounding temperature. Normally installed in commercial applications, SR Trace helps provide maximum freeze protection for pipes and vessels in ambient temperatures down to -40°F/-40°C. Use SR Trace cables to prevent water pipes from freezing, to maintain liquids in pipes at a constant temperature in order to prevent degradation of the liquid, or to maintain viscosity for flow conditions. SR Trace can be installed in dry or wet environments. Available in power densities of 3, 5, and 8 watts per foot at 50°F/10°C, for both 120 Vac and 240 Vac applications. 240 Vac can be used for 208 Vac or 277 Vac applications. SR Trace cables are UL Listed to US and Canadian Safety Standards and CSA Certified. See item specific certifications below.

CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
SR31CB	3 w/ft, 120 Vac, cut-to-order	-	-	-	 
JP31CB	3 w/ft, 120 Vac Job Pack (100' cable, 2-SRP,1-SRST,1-SRTCS)	1	8	0-13627-06931-2	
SR32CB	3 w/ft, 240 Vac, cut-to-order	-	-	-	
JP32CB	3 w/ft, 240 Vac Job Pack (100' cable, 2-SRP,1-SRST,1-SRTCS)	1	8	0-13627-06932-9	
SR51CB	5 w/ft, 120 Vac, cut-to-order	-	-	-	
JP51CB	5 w/ft, 120 Vac Job Pack (100' cable, 2-SRP,1-SRST,1-SRTCS)	1	8	0-13627-06930-5	
SR52CB	5 w/ft, 240 Vac, cut-to-order	-	-	-	
JP52CB	5 w/ft, 240 Vac Job Pack (100' cable, 2-SRP,1-SRST,1-SRTCS)	1	8	0-13627-06929-9	
SR81CB	8 w/ft, 120 Vac, cut-to-order	-	-	-	
SR82CB	8 w/ft, 240 Vac, cut-to-order	-	-	-	
SR31J	3 w/ft, 120 Vac, cut-to-order	-	-	-	
SR31J250	250' self-dispensing reel	1	20	0-13627-06925-1	
SR32J	3 w/ft, 240 Vac, cut-to-order	-	-	-	
SR32J250	250' self-dispensing reel	1	20	0-13627-06923-7	
SR51J	5 w/ft, 120 Vac, cut-to-order	-	-	-	
SR51J250	SR51J on a 250' Reel	1	20	0-13627-06921-3	
SR51J750	750' self-dispensing reel	1	72	0-13627-06922-0	
JP51J	5 w/ft, 120 Vac Job Pack (100' cable, 2-SRP,1-SRST,1-SRTCS)	1	8	0-13627-06927-5	
SR52J	5 w/ft, 240 Vac, cut-to-order	-	-	-	
SR52J250	SR52J on a 250' Reel	1	20	0-13627-06919-0	
SR52J750	750' self-dispensing reel	1	72	0-13627-06920-6	
JP52J	5 w/ft, 240 Vac Job Pack (100' cable, 2-SRP,1-SRST,1-SRTCS)	1	8	0-13627-06928-2	
SR81J	8 w/ft, 120 Vac, cut-to-order	-	-	-	
SR81J250	250' self-dispensing reel	1	20	0-13627-06917-6	
SR82J	8 w/ft, 240 Vac, cut-to-order	-	-	-	
SR82J250	250' self-dispensing reel	1	20	0-13627-06815-2	

SR TRACE ACCESSORIES

Specially designed kits ease installation and connection of SR Trace products. SR Trace accessories are UL Listed and CSA Certified.



CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
SRP	Heat shrink power/end connection kit	1	3	0-13627-06947-3	 
SRST	Heat shrink splice and "T" connection kit	2	2	0-13627-06959-6	
SRES	Heat shrink end seal kit	5	2	0-13627-06968-8	
SRTCS	Fiberglass application tape and caution signs	1	2	0-13627-06970-1	