

Spiral Wrap



- Harness multiple cables into a single manageable bundle
- Allows breakouts of single/multiple cables
- Provides abrasion protection for wire, cables, hoses, and tubing
- Reverse cut
- Multiple colors allow easy identification of cable bundles
- Installation tool supplied in each package
- Available in multiple materials
- Reusable
- UL File: E141152
- Voltage Rating: 600 V

| Part Number | Material* | Color | Length Per Reel | | Bundle Diameter Range | | Outside Diameter | | Temperature Range | Wall Thickness | | Std. Pkg. Qty.‡ |
|-------------|--------------|---------|-----------------|-------|-----------------------|-------------|------------------|------|---------------------------------|----------------|------|-----------------|
| | | | Ft. | m | In. | mm | In. | mm | | In. | mm | |
| T12F-C | Polyethylene | Natural | 100 | 30.5 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -40°F – 122°F (-40°C – 50°C) | 0.030 | 0.76 | 1 |
| T12F-D | Polyethylene | Natural | 500 | 152.4 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -40°F – 122°F (-40°C – 50°C) | 0.030 | 0.76 | 1 |
| T19F-C | Polyethylene | Natural | 100 | 30.5 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -40°F – 122°F (-40°C – 50°C) | 0.035 | 0.89 | 1 |
| T19F-M | Polyethylene | Natural | 1,000 | 304.8 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -40°F – 122°F (-40°C – 50°C) | 0.035 | 0.89 | 1 |
| T25F-C | Polyethylene | Natural | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C1 | Polyethylene | Brown | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C2 | Polyethylene | Red | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C3Y | Polyethylene | Orange | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C4Y | Polyethylene | Yellow | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C5 | Polyethylene | Green | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C6 | Polyethylene | Blue | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C7 | Polyethylene | Purple | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C8 | Polyethylene | Gray | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C10 | Polyethylene | White | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C16 | Polyethylene | Pink | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-M | Polyethylene | Natural | 1,000 | 304.8 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T38F-C | Polyethylene | Natural | 100 | 30.5 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 122°F (-40°C – 50°C) | 0.055 | 1.40 | 1 |
| T38F-TL | Polyethylene | Natural | 250 | 76.2 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 122°F (-40°C – 50°C) | 0.055 | 1.40 | 1 |
| T50F-X | Polyethylene | Natural | 10 | 3.1 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C | Polyethylene | Natural | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C1 | Polyethylene | Brown | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C2 | Polyethylene | Red | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C3Y | Polyethylene | Orange | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C4Y | Polyethylene | Yellow | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C5 | Polyethylene | Green | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |

*Flame retardant products are manufactured from a material that is rated UL 94V-0.

‡Reel packaging may contain splices. Contact Panduit Customer Service for further information.

Continues on next page

Spiral Wrap (continued)

| Part Number | Material* | Color | Length Per Reel | | Bundle Diameter Range | | Outside Diameter | | Temperature Range | Wall Thickness | | Std. Pkg. Qty. ‡ |
|-------------|--------------------------------|---------|-----------------|-------|-----------------------|--------------|------------------|------|------------------------------|----------------|------|------------------|
| | | | Ft. | m | In. | mm | In. | mm | | In. | mm | |
| T50F-C6 | Polyethylene | Blue | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C7 | Polyethylene | Purple | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C8 | Polyethylene | Gray | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C10 | Polyethylene | White | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C16 | Polyethylene | Pink | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-TL | Polyethylene | Natural | 250 | 76.2 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-TL4Y | Polyethylene | Yellow | 250 | 76.2 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T62F-C | Polyethylene | Natural | 100 | 30.5 | 1/2 – 4 1/2 | 12.7 – 114.3 | 0.62 | 15.9 | -40°F – 122°F (-40°C – 50°C) | 0.062 | 1.57 | 1 |
| T62F-TL | Polyethylene | Natural | 250 | 76.2 | 1/2 – 4 1/2 | 12.7 – 114.3 | 0.62 | 15.9 | -40°F – 122°F (-40°C – 50°C) | 0.062 | 1.57 | 1 |
| T75F-C | Polyethylene | Natural | 100 | 30.5 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -40°F – 122°F (-40°C – 50°C) | 0.065 | 1.65 | 1 |
| T75F-T | Polyethylene | Natural | 200 | 61.0 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -40°F – 122°F (-40°C – 50°C) | 0.065 | 1.65 | 1 |
| T100F-C | Polyethylene | Natural | 100 | 30.5 | 7/8 – 6 | 22.2 – 152.4 | 1.00 | 25.4 | -40°F – 122°F (-40°C – 50°C) | 0.070 | 1.78 | 1 |
| T12F-C0 | Weather Resistant Polyethylene | Black | 100 | 30.5 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -40°F – 122°F (-40°C – 50°C) | 0.030 | 0.76 | 1 |
| T12F-D0 | Weather Resistant Polyethylene | Black | 500 | 152.4 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -40°F – 122°F (-40°C – 50°C) | 0.030 | 0.76 | 1 |
| T19F-C0 | Weather Resistant Polyethylene | Black | 100 | 30.5 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -40°F – 122°F (-40°C – 50°C) | 0.035 | 0.89 | 1 |
| T25F-X0 | Weather Resistant Polyethylene | Black | 10 | 3.1 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C0 | Weather Resistant Polyethylene | Black | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-M0 | Weather Resistant Polyethylene | Black | 1,000 | 304.8 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T38F-C0 | Weather Resistant Polyethylene | Black | 100 | 30.5 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 122°F (-40°C – 50°C) | 0.055 | 1.40 | 1 |
| T38F-TL0 | Weather Resistant Polyethylene | Black | 250 | 76.2 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 122°F (-40°C – 50°C) | 0.055 | 1.40 | 1 |
| T50F-X0 | Weather Resistant Polyethylene | Black | 10 | 3.1 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C0 | Weather Resistant Polyethylene | Black | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-TL0 | Weather Resistant Polyethylene | Black | 250 | 76.2 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |

*Flame retardant products are manufactured from a material that is rated UL 94V-0.
 ‡Reel packaging may contain splices. Contact Panduit Customer Service for further information.

Continues on next page

Spiral Wrap (continued)

| Part Number | Material* | Color | Length Per Reel | | Bundle Diameter Range | | Outside Diameter | | Temperature Range | Wall Thickness | | Std. Pkg. Qty.‡ |
|-------------|--------------------------------|---------|-----------------|-------|-----------------------|--------------|------------------|------|---------------------------------|----------------|------|-----------------|
| | | | Ft. | m | In. | mm | In. | mm | | In. | mm | |
| T62F-C0 | Weather Resistant Polyethylene | Black | 100 | 30.5 | 1/2 – 4 1/2 | 12.7 – 114.3 | 0.62 | 15.9 | -40°F – 122°F (-40°C – 50°C) | 0.062 | 1.57 | 1 |
| T62F-TL0 | Weather Resistant Polyethylene | Black | 250 | 76.2 | 1/2 – 4 1/2 | 12.7 – 114.3 | 0.62 | 15.9 | -40°F – 122°F (-40°C – 50°C) | 0.062 | 1.57 | 1 |
| T75F-C0 | Weather Resistant Polyethylene | Black | 100 | 30.5 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -40°F – 122°F (-40°C – 50°C) | 0.065 | 1.65 | 1 |
| T75F-T0 | Weather Resistant Polyethylene | Black | 200 | 61.0 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -40°F – 122°F (-40°C – 50°C) | 0.065 | 1.65 | 1 |
| T100F-C0 | Weather Resistant Polyethylene | Black | 100 | 30.5 | 7/8 – 6 | 22.2 – 152.4 | 1.00 | 25.4 | -40°F – 122°F (-40°C – 50°C) | 0.070 | 1.78 | 1 |
| T12R-CY | Fire Resistant Polyethylene | Natural | 100 | 30.5 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -40°F – 122°F (-40°C – 50°C) | 0.030 | 0.76 | 1 |
| T19R-CY | Fire Resistant Polyethylene | Natural | 100 | 30.5 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -40°F – 122°F (-40°C – 50°C) | 0.035 | 0.89 | 1 |
| T25R-CY | Fire Resistant Polyethylene | Natural | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25R-C20Y | Fire Resistant Polyethylene | Black | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25R-MY | Fire Resistant Polyethylene | Natural | 1,000 | 304.8 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25R-M20Y | Fire Resistant Polyethylene | Black | 1,000 | 304.8 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T38R-CY | Fire Resistant Polyethylene | Natural | 100 | 30.5 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 122°F (-40°C – 50°C) | 0.055 | 1.40 | 1 |
| T38R-TLY | Fire Resistant Polyethylene | Natural | 250 | 76.2 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 122°F (-40°C – 50°C) | 0.055 | 1.40 | 1 |
| T50R-CY | Fire Resistant Polyethylene | Natural | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50R-TLY | Fire Resistant Polyethylene | Natural | 250 | 76.2 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T62R-CY | Fire Resistant Polyethylene | Natural | 100 | 30.5 | 1/2 – 4 1/2 | 12.7 – 114.3 | 0.62 | 15.9 | -40°F – 122°F (-40°C – 50°C) | 0.062 | 1.57 | 1 |
| T75R-CY | Fire Resistant Polyethylene | Natural | 100 | 30.5 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -40°F – 122°F (-40°C – 50°C) | 0.065 | 1.65 | 1 |
| T100R-CY | Fire Resistant Polyethylene | Natural | 100 | 30.5 | 7/8 – 6 | 22.2 – 152.4 | 1.00 | 25.4 | -40°F – 122°F (-40°C – 50°C) | 0.070 | 1.78 | 1 |
| T12FR-CY | Flame Retardant Polyethylene | Natural | 100 | 30.5 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -4°F – 122°F (-20°C – 50°C) | 0.030 | 0.76 | 1 |
| T12FR-C20Y | Flame Retardant Polyethylene | Black | 100 | 30.5 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -4°F – 122°F (-20°C – 50°C) | 0.030 | 0.76 | 1 |
| T19FR-CY | Flame Retardant Polyethylene | Natural | 100 | 30.5 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -4°F – 122°F (-20°C – 50°C) | 0.032 | 0.80 | 1 |
| T19FR-C20Y | Flame Retardant Polyethylene | Black | 100 | 30.5 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -4°F – 122°F (-20°C – 50°C) | 0.032 | 0.80 | 1 |
| T25FR-CY | Flame Retardant Polyethylene | Natural | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -4°F – 122°F (-20°C – 50°C) | 0.040 | 1.02 | 1 |
| T25FR-C20Y | Flame Retardant Polyethylene | Black | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -4°F – 122°F (-20°C – 50°C) | 0.040 | 1.02 | 1 |

*Flame retardant products are manufactured from a material that is rated UL 94V-0.

‡Reel packaging may contain splices. Contact Panduit Customer Service for further information.

Continues on next page

Spiral Wrap (continued)

| Part Number | Material* | Color | Length Per Reel | | Bundle Diameter Range | | Outside Diameter | | Temperature Range | Wall Thickness | | Std. Pkg. Qty. ‡ |
|-------------|------------------------------|---------|-----------------|-------|-----------------------|--------------|------------------|------|------------------------------|----------------|------|------------------|
| | | | Ft. | m | In. | mm | In. | mm | | In. | mm | |
| T25FR-MY | Flame Retardant Polyethylene | Natural | 1,000 | 304.8 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -4°F – 122°F (-20°C – 50°C) | 0.040 | 1.02 | 1 |
| T25FR-M20Y | Flame Retardant Polyethylene | Black | 1,000 | 304.8 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -4°F – 122°F (-20°C – 50°C) | 0.040 | 1.02 | 1 |
| T38FR-CY | Flame Retardant Polyethylene | Natural | 100 | 30.5 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -4°F – 122°F (-20°C – 50°C) | 0.055 | 1.40 | 1 |
| T38FR-C20Y | Flame Retardant Polyethylene | Black | 100 | 30.5 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -4°F – 122°F (-20°C – 50°C) | 0.055 | 1.40 | 1 |
| T38FR-TLY | Flame Retardant Polyethylene | Natural | 250 | 76.2 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -4°F – 122°F (-20°C – 50°C) | 0.055 | 1.40 | 1 |
| T50FR-CY | Flame Retardant Polyethylene | Natural | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -4°F – 122°F (-20°C – 50°C) | 0.060 | 1.52 | 1 |
| T50FR-C20Y | Flame Retardant Polyethylene | Black | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -4°F – 122°F (-20°C – 50°C) | 0.060 | 1.52 | 1 |
| T50FR-TLY | Flame Retardant Polyethylene | Natural | 250 | 76.2 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -4°F – 122°F (-20°C – 50°C) | 0.060 | 1.52 | 1 |
| T62FR-CY | Flame Retardant Polyethylene | Natural | 100 | 30.5 | 1/2 – 4 1/2 | 12.7 – 114.3 | 0.62 | 15.9 | -4°F – 122°F (-20°C – 50°C) | 0.062 | 1.57 | 1 |
| T62FR-C20Y | Flame Retardant Polyethylene | Black | 100 | 30.5 | 1/2 – 4 1/2 | 12.7 – 114.3 | 0.62 | 15.9 | -4°F – 122°F (-20°C – 50°C) | 0.062 | 1.57 | 1 |
| T75FR-CY | Flame Retardant Polyethylene | Natural | 100 | 30.5 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -4°F – 122°F (-20°C – 50°C) | 0.065 | 1.65 | 1 |
| T75FR-C20Y | Flame Retardant Polyethylene | Black | 100 | 30.5 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -4°F – 122°F (-20°C – 50°C) | 0.065 | 1.65 | 1 |
| T75FR-TY | Flame Retardant Polyethylene | Natural | 200 | 61.0 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -4°F – 122°F (-20°C – 50°C) | 0.065 | 1.65 | 1 |
| T100FR-CY | Flame Retardant Polyethylene | Natural | 100 | 30.5 | 7/8 – 6 | 22.2 – 152.4 | 1.00 | 25.4 | -4°F – 122°F (-20°C – 50°C) | 0.070 | 1.78 | 1 |
| T100FR-C20Y | Flame Retardant Polyethylene | Black | 100 | 30.5 | 7/8 – 6 | 22.2 – 152.4 | 1.00 | 25.4 | -4°F – 122°F (-20°C – 50°C) | 0.070 | 1.78 | 1 |
| T12N-C | Nylon 6.6 | Natural | 100 | 30.5 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -40°F – 149°F (-40°C – 65°C) | 0.015 | 0.38 | 1 |
| T12N-D | Nylon 6.6 | Natural | 500 | 152.4 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -40°F – 149°F (-40°C – 65°C) | 0.015 | 0.38 | 1 |
| T19N-C | Nylon 6.6 | Natural | 100 | 30.5 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -40°F – 149°F (-40°C – 65°C) | 0.020 | 0.51 | 1 |
| T19N-M | Nylon 6.6 | Natural | 1,000 | 304.8 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -40°F – 149°F (-40°C – 65°C) | 0.020 | 0.51 | 1 |
| T25N-C | Nylon 6.6 | Natural | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 149°F (-40°C – 65°C) | 0.023 | 0.58 | 1 |
| T25N-M | Nylon 6.6 | Natural | 1,000 | 304.8 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 149°F (-40°C – 65°C) | 0.023 | 0.58 | 1 |
| T38N-C | Nylon 6.6 | Natural | 100 | 30.5 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 149°F (-40°C – 65°C) | 0.030 | 0.76 | 1 |
| T38N-TL | Nylon 6.6 | Natural | 250 | 76.2 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 149°F (-40°C – 65°C) | 0.030 | 0.76 | 1 |

*Flame retardant products are manufactured from a material that is rated UL 94V-0.
 ‡Reel packaging may contain splices. Contact Panduit Customer Service for further information.
 ^TFE is Polytetrafluorethylene material.

Continues on next page

Spiral Wrap (continued)

| Part Number | Material* | Color | Length Per Reel | | Bundle Diameter Range | | Outside Diameter | | Temperature Range | Wall Thickness | | Std. Pkg. Qty.‡ |
|-------------|--|---------|-----------------|-------|-----------------------|--------------|------------------|------|---------------------------------|----------------|------|-----------------|
| | | | Ft. | m | In. | mm | In. | mm | | In. | mm | |
| T50N-C | Nylon 6.6 | Natural | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 149°F (-40°C – 65°C) | 0.032 | 0.81 | 1 |
| T50N-TL | Nylon 6.6 | Natural | 250 | 76.2 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 149°F (-40°C – 65°C) | 0.032 | 0.81 | 1 |
| T62N-C | Nylon 6.6 | Natural | 100 | 30.5 | 1/2 – 4 1/2 | 12.7 – 114.3 | 0.62 | 15.9 | -40°F – 149°F (-40°C – 65°C) | 0.035 | 0.89 | 1 |
| T75N-C | Nylon 6.6 | Natural | 100 | 30.5 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -40°F – 149°F (-40°C – 65°C) | 0.040 | 1.02 | 1 |
| T75N-T | Nylon 6.6 | Natural | 200 | 61 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -40°F – 149°F (-40°C – 65°C) | 0.040 | 1.02 | 1 |
| T100N-C | Nylon 6.6 | Natural | 100 | 30.5 | 7/8 – 6 | 22.2 – 152.4 | 1.00 | 25.4 | -40°F – 149°F (-40°C – 65°C) | 0.045 | 1.14 | 1 |
| T12N-C0 | Weather Resistant Nylon 6.6 | Black | 100 | 30.5 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -40°F – 149°F (-40°C – 65°C) | 0.015 | 0.38 | 1 |
| T19N-C0 | Weather Resistant Nylon 6.6 | Black | 100 | 30.5 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -40°F – 149°F (-40°C – 65°C) | 0.020 | 0.51 | 1 |
| T19N-M0 | Weather Resistant Nylon 6.6 | Black | 1,000 | 304.8 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -40°F – 149°F (-40°C – 65°C) | 0.020 | 0.51 | 1 |
| T25N-M0 | Weather Resistant Nylon 6.6 | Black | 1,000 | 304.8 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 149°F (-40°C – 65°C) | 0.023 | 0.58 | 1 |
| T25N-C0 | Weather Resistant Nylon 6.6 | Black | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.4 | 0.25 | 6.4 | -40°F – 149°F (-40°C – 65°C) | 0.023 | 0.58 | 1 |
| T38N-C0 | Weather Resistant Nylon 6.6 | Black | 100 | 30.5 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 149°F (-40°C – 65°C) | 0.030 | 0.76 | 1 |
| T50N-C0 | Weather Resistant Nylon 6.6 | Black | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 149°F (-40°C – 65°C) | 0.032 | 0.81 | 1 |
| T50N-TL0 | Weather Resistant Nylon 6.6 | Black | 250 | 76.2 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 149°F (-40°C – 65°C) | 0.032 | 0.81 | 1 |
| T62N-C0 | Weather Resistant Nylon 6.6 | Black | 100 | 30.5 | 1/2 – 4 1/2 | 12.7 – 114.3 | 0.62 | 15.9 | -40°F – 149°F (-40°C – 65°C) | 0.035 | 0.89 | 1 |
| T75N-C0 | Weather Resistant Nylon 6.6 | Black | 100 | 30.5 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -40°F – 149°F (-40°C – 65°C) | 0.040 | 1.02 | 1 |
| T100N-C0 | Weather Resistant Nylon 6.6 | Black | 100 | 30.5 | 7/8 – 6 | 22.2 – 152.4 | 1.00 | 25.4 | -40°F – 149°F (-40°C – 65°C) | 0.045 | 1.14 | 1 |
| T25NZFR-C20 | Low Smoke Halogen-Free Flame-Retardant Nylon | Black | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 149°F (-40°C – 65°C) | 0.023 | 0.58 | 1 |
| T38NZFR-C20 | Low Smoke Halogen-Free Flame-Retardant Nylon | Black | 100 | 30.5 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 149°F (-40°C – 65°C) | 0.030 | 0.76 | 1 |
| T50NZFR-C20 | Low Smoke Halogen-Free Flame-Retardant Nylon | Black | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 149°F (-40°C – 65°C) | 0.032 | 0.81 | 1 |

*Flame retardant products are manufactured from a material that is rated UL 94V-0.

‡Reel packaging may contain splices. Contact Panduit Customer Service for further information.

^TFE is Polytetrafluorethylene material.

Continues on next page

Spiral Wrap (continued)

| Part Number | Material* | Color | Length Per Reel | | Bundle Diameter Range | | Outside Diameter | | Temperature Range | Wall Thickness | | Std. Pkg. Qty.‡ |
|-------------|--|---------|-----------------|------|-----------------------|--------------|------------------|------|------------------------------------|----------------|------|-----------------|
| | | | Ft. | m | In. | mm | In. | mm | | In. | mm | |
| T75NZFR-C20 | Low Smoke Halogen-Free Flame-Retardant Nylon | Black | 100 | 30.5 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -40°F – 149°F (-40°C – 65°C) | 0.040 | 1.02 | 1 |
| T38P-C0 | Weather Resistant Polypropylene | Black | 100 | 30.5 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 239°F (-40°C – 115°C) | 0.030 | 0.76 | 1 |
| T50P-C0 | Weather Resistant Polypropylene | Black | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 239°F (-40°C – 115°C) | 0.030 | 0.76 | 1 |
| T100P-C0 | Weather Resistant Polypropylene | Black | 100 | 30.5 | 7/8 – 6 | 22.2 – 152.4 | 1.00 | 25.4 | -40°F – 239°F (-40°C – 115°C) | 0.030 | 0.76 | 1 |
| T12T-C | TFE^ | Natural | 100 | 30.5 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -454°F – 356°F (-270°C – 180°C) | 0.020 | 0.51 | 1 |
| T19T-C | TFE^ | Natural | 100 | 30.5 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -454°F – 356°F (-270°C – 180°C) | 0.030 | 0.76 | 1 |
| T25T-L | TFE^ | Natural | 50 | 15.2 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -454°F – 356°F (-270°C – 180°C) | 0.030 | 0.76 | 1 |
| T25T-L0 | TFE^ | Black | 50 | 15.2 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -454°F – 356°F (-270°C – 180°C) | 0.030 | 0.76 | 1 |
| T38T-L | TFE^ | Natural | 50 | 15.2 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -454°F – 356°F (-270°C – 180°C) | 0.030 | 0.76 | 1 |
| T50T-Q | TFE^ | Natural | 25 | 7.6 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -454°F – 356°F (-270°C – 180°C) | 0.030 | 0.76 | 1 |
| T62T-Q | TFE^ | Natural | 25 | 7.6 | 1/2 – 4 1/2 | 12.7 – 114.3 | 0.62 | 15.9 | -454°F – 356°F (-270°C – 180°C) | 0.030 | 0.76 | 1 |
| T75T-X | TFE^ | Natural | 10 | 3.1 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -454°F – 356°F (-270°C – 180°C) | 0.030 | 0.76 | 1 |
| T100T-X | TFE^ | Natural | 10 | 3.1 | 7/8 – 6 | 22.2 – 152.4 | 1.00 | 25.4 | -454°F – 356°F (-270°C – 180°C) | 0.040 | 1.02 | 1 |

*Flame retardant products are manufactured from a material that is rated UL 94V-0.

‡Reel packaging may contain splices. Contact Panduit Customer Service for further information.

^TFE is Polytetrafluorethylene material.

B1.
Cable
TiesB2.
Cable
AccessoriesB3.
Stainless
Steel Cable
Ties &
AccessoriesC1.
Wiring
DuctC2.
Abrasion
ProtectionC3.
Cable
ManagementD1.
TerminalsD2.
Power
ConnectorsD3.
Grounding
ConnectorsE1.
Labeling
SystemsE2.
LabelsE3.
Pre-Printed
&
Write-On
MarkersE4.
Permanent
IdentificationE5.
Industrial
Safety
SolutionsF.
Keystone
Cabling
SystemsG.
Part
Number
Index

Spiral Wrap



- Harness multiple cables into a single manageable bundle
- Allows breakouts of single/multiple cables
- Provides abrasion protection for wire, cables, hoses, and tubing
- Reverse cut
- Multiple colors allow easy identification of cable bundles
- Installation tool supplied in each package
- Available in multiple materials
- Reusable
- UL File: E141152
- Voltage Rating: 600 V

| Part Number | Material* | Color | Length Per Reel | | Bundle Diameter Range | | Outside Diameter | | Temperature Range | Wall Thickness | | Std. Pkg. Qty.‡ |
|-------------|--------------|---------|-----------------|-------|-----------------------|-------------|------------------|------|---------------------------------|----------------|------|-----------------|
| | | | Ft. | m | In. | mm | In. | mm | | In. | mm | |
| T12F-C | Polyethylene | Natural | 100 | 30.5 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -40°F – 122°F (-40°C – 50°C) | 0.030 | 0.76 | 1 |
| T12F-D | Polyethylene | Natural | 500 | 152.4 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -40°F – 122°F (-40°C – 50°C) | 0.030 | 0.76 | 1 |
| T19F-C | Polyethylene | Natural | 100 | 30.5 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -40°F – 122°F (-40°C – 50°C) | 0.035 | 0.89 | 1 |
| T19F-M | Polyethylene | Natural | 1,000 | 304.8 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -40°F – 122°F (-40°C – 50°C) | 0.035 | 0.89 | 1 |
| T25F-C | Polyethylene | Natural | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C1 | Polyethylene | Brown | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C2 | Polyethylene | Red | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C3Y | Polyethylene | Orange | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C4Y | Polyethylene | Yellow | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C5 | Polyethylene | Green | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C6 | Polyethylene | Blue | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C7 | Polyethylene | Purple | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C8 | Polyethylene | Gray | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C10 | Polyethylene | White | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C16 | Polyethylene | Pink | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-M | Polyethylene | Natural | 1,000 | 304.8 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T38F-C | Polyethylene | Natural | 100 | 30.5 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 122°F (-40°C – 50°C) | 0.055 | 1.40 | 1 |
| T38F-TL | Polyethylene | Natural | 250 | 76.2 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 122°F (-40°C – 50°C) | 0.055 | 1.40 | 1 |
| T50F-X | Polyethylene | Natural | 10 | 3.1 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C | Polyethylene | Natural | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C1 | Polyethylene | Brown | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C2 | Polyethylene | Red | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C3Y | Polyethylene | Orange | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C4Y | Polyethylene | Yellow | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C5 | Polyethylene | Green | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |

*Flame retardant products are manufactured from a material that is rated UL 94V-0.
‡Reel packaging may contain splices. Contact Panduit Customer Service for further information.

Continues on next page

Spiral Wrap (continued)

| Part Number | Material* | Color | Length Per Reel | | Bundle Diameter Range | | Outside Diameter | | Temperature Range | Wall Thickness | | Std. Pkg. Qty.‡ |
|-------------|--------------------------------|---------|-----------------|-------|-----------------------|--------------|------------------|------|------------------------------|----------------|------|-----------------|
| | | | Ft. | m | In. | mm | In. | mm | | In. | mm | |
| T50F-C6 | Polyethylene | Blue | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C7 | Polyethylene | Purple | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C8 | Polyethylene | Gray | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C10 | Polyethylene | White | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C16 | Polyethylene | Pink | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-TL | Polyethylene | Natural | 250 | 76.2 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-TL4Y | Polyethylene | Yellow | 250 | 76.2 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T62F-C | Polyethylene | Natural | 100 | 30.5 | 1/2 – 4 1/2 | 12.7 – 114.3 | 0.62 | 15.9 | -40°F – 122°F (-40°C – 50°C) | 0.062 | 1.57 | 1 |
| T62F-TL | Polyethylene | Natural | 250 | 76.2 | 1/2 – 4 1/2 | 12.7 – 114.3 | 0.62 | 15.9 | -40°F – 122°F (-40°C – 50°C) | 0.062 | 1.57 | 1 |
| T75F-C | Polyethylene | Natural | 100 | 30.5 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -40°F – 122°F (-40°C – 50°C) | 0.065 | 1.65 | 1 |
| T75F-T | Polyethylene | Natural | 200 | 61.0 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -40°F – 122°F (-40°C – 50°C) | 0.065 | 1.65 | 1 |
| T100F-C | Polyethylene | Natural | 100 | 30.5 | 7/8 – 6 | 22.2 – 152.4 | 1.00 | 25.4 | -40°F – 122°F (-40°C – 50°C) | 0.070 | 1.78 | 1 |
| T12F-C0 | Weather Resistant Polyethylene | Black | 100 | 30.5 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -40°F – 122°F (-40°C – 50°C) | 0.030 | 0.76 | 1 |
| T12F-D0 | Weather Resistant Polyethylene | Black | 500 | 152.4 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -40°F – 122°F (-40°C – 50°C) | 0.030 | 0.76 | 1 |
| T19F-C0 | Weather Resistant Polyethylene | Black | 100 | 30.5 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -40°F – 122°F (-40°C – 50°C) | 0.035 | 0.89 | 1 |
| T25F-X0 | Weather Resistant Polyethylene | Black | 10 | 3.1 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-C0 | Weather Resistant Polyethylene | Black | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25F-M0 | Weather Resistant Polyethylene | Black | 1,000 | 304.8 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T38F-C0 | Weather Resistant Polyethylene | Black | 100 | 30.5 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 122°F (-40°C – 50°C) | 0.055 | 1.40 | 1 |
| T38F-TL0 | Weather Resistant Polyethylene | Black | 250 | 76.2 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 122°F (-40°C – 50°C) | 0.055 | 1.40 | 1 |
| T50F-X0 | Weather Resistant Polyethylene | Black | 10 | 3.1 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-C0 | Weather Resistant Polyethylene | Black | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50F-TL0 | Weather Resistant Polyethylene | Black | 250 | 76.2 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |

*Flame retardant products are manufactured from a material that is rated UL 94V-0.
 ‡Reel packaging may contain splices. Contact Panduit Customer Service for further information.

Continues on next page

Spiral Wrap (continued)

| Part Number | Material* | Color | Length Per Reel | | Bundle Diameter Range | | Outside Diameter | | Temperature Range | Wall Thickness | | Std. Pkg. Qty.‡ |
|-------------|--------------------------------|---------|-----------------|-------|-----------------------|--------------|------------------|------|---------------------------------|----------------|------|-----------------|
| | | | Ft. | m | In. | mm | In. | mm | | In. | mm | |
| T62F-C0 | Weather Resistant Polyethylene | Black | 100 | 30.5 | 1/2 – 4 1/2 | 12.7 – 114.3 | 0.62 | 15.9 | -40°F – 122°F (-40°C – 50°C) | 0.062 | 1.57 | 1 |
| T62F-TL0 | Weather Resistant Polyethylene | Black | 250 | 76.2 | 1/2 – 4 1/2 | 12.7 – 114.3 | 0.62 | 15.9 | -40°F – 122°F (-40°C – 50°C) | 0.062 | 1.57 | 1 |
| T75F-C0 | Weather Resistant Polyethylene | Black | 100 | 30.5 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -40°F – 122°F (-40°C – 50°C) | 0.065 | 1.65 | 1 |
| T75F-T0 | Weather Resistant Polyethylene | Black | 200 | 61.0 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -40°F – 122°F (-40°C – 50°C) | 0.065 | 1.65 | 1 |
| T100F-C0 | Weather Resistant Polyethylene | Black | 100 | 30.5 | 7/8 – 6 | 22.2 – 152.4 | 1.00 | 25.4 | -40°F – 122°F (-40°C – 50°C) | 0.070 | 1.78 | 1 |
| T12R-CY | Fire Resistant Polyethylene | Natural | 100 | 30.5 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -40°F – 122°F (-40°C – 50°C) | 0.030 | 0.76 | 1 |
| T19R-CY | Fire Resistant Polyethylene | Natural | 100 | 30.5 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -40°F – 122°F (-40°C – 50°C) | 0.035 | 0.89 | 1 |
| T25R-CY | Fire Resistant Polyethylene | Natural | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25R-C20Y | Fire Resistant Polyethylene | Black | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25R-MY | Fire Resistant Polyethylene | Natural | 1,000 | 304.8 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T25R-M20Y | Fire Resistant Polyethylene | Black | 1,000 | 304.8 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 122°F (-40°C – 50°C) | 0.040 | 1.02 | 1 |
| T38R-CY | Fire Resistant Polyethylene | Natural | 100 | 30.5 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 122°F (-40°C – 50°C) | 0.055 | 1.40 | 1 |
| T38R-TLY | Fire Resistant Polyethylene | Natural | 250 | 76.2 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 122°F (-40°C – 50°C) | 0.055 | 1.40 | 1 |
| T50R-CY | Fire Resistant Polyethylene | Natural | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T50R-TLY | Fire Resistant Polyethylene | Natural | 250 | 76.2 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 0.060 | 1.52 | 1 |
| T62R-CY | Fire Resistant Polyethylene | Natural | 100 | 30.5 | 1/2 – 4 1/2 | 12.7 – 114.3 | 0.62 | 15.9 | -40°F – 122°F (-40°C – 50°C) | 0.062 | 1.57 | 1 |
| T75R-CY | Fire Resistant Polyethylene | Natural | 100 | 30.5 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -40°F – 122°F (-40°C – 50°C) | 0.065 | 1.65 | 1 |
| T100R-CY | Fire Resistant Polyethylene | Natural | 100 | 30.5 | 7/8 – 6 | 22.2 – 152.4 | 1.00 | 25.4 | -40°F – 122°F (-40°C – 50°C) | 0.070 | 1.78 | 1 |
| T12FR-CY | Flame Retardant Polyethylene | Natural | 100 | 30.5 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -4°F – 122°F (-20°C – 50°C) | 0.030 | 0.76 | 1 |
| T12FR-C20Y | Flame Retardant Polyethylene | Black | 100 | 30.5 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -4°F – 122°F (-20°C – 50°C) | 0.030 | 0.76 | 1 |
| T19FR-CY | Flame Retardant Polyethylene | Natural | 100 | 30.5 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -4°F – 122°F (-20°C – 50°C) | 0.032 | 0.80 | 1 |
| T19FR-C20Y | Flame Retardant Polyethylene | Black | 100 | 30.5 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -4°F – 122°F (-20°C – 50°C) | 0.032 | 0.80 | 1 |
| T25FR-CY | Flame Retardant Polyethylene | Natural | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -4°F – 122°F (-20°C – 50°C) | 0.040 | 1.02 | 1 |
| T25FR-C20Y | Flame Retardant Polyethylene | Black | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -4°F – 122°F (-20°C – 50°C) | 0.040 | 1.02 | 1 |

*Flame retardant products are manufactured from a material that is rated UL 94V-0.

‡Reel packaging may contain splices. Contact Panduit Customer Service for further information.

Continues on next page

Spiral Wrap (continued)

| Part Number | Material* | Color | Length Per Reel | | Bundle Diameter Range | | Outside Diameter | | Temperature Range | Wall Thickness | | Std. Pkg. Qty. ‡ |
|-------------|------------------------------|---------|-----------------|-------|-----------------------|--------------|------------------|------|------------------------------|----------------|------|------------------|
| | | | Ft. | m | In. | mm | In. | mm | | In. | mm | |
| T25FR-MY | Flame Retardant Polyethylene | Natural | 1,000 | 304.8 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -4°F – 122°F (-20°C – 50°C) | 0.040 | 1.02 | 1 |
| T25FR-M20Y | Flame Retardant Polyethylene | Black | 1,000 | 304.8 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -4°F – 122°F (-20°C – 50°C) | 0.040 | 1.02 | 1 |
| T38FR-CY | Flame Retardant Polyethylene | Natural | 100 | 30.5 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -4°F – 122°F (-20°C – 50°C) | 0.055 | 1.40 | 1 |
| T38FR-C20Y | Flame Retardant Polyethylene | Black | 100 | 30.5 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -4°F – 122°F (-20°C – 50°C) | 0.055 | 1.40 | 1 |
| T38FR-TLY | Flame Retardant Polyethylene | Natural | 250 | 76.2 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -4°F – 122°F (-20°C – 50°C) | 0.055 | 1.40 | 1 |
| T50FR-CY | Flame Retardant Polyethylene | Natural | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -4°F – 122°F (-20°C – 50°C) | 0.060 | 1.52 | 1 |
| T50FR-C20Y | Flame Retardant Polyethylene | Black | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -4°F – 122°F (-20°C – 50°C) | 0.060 | 1.52 | 1 |
| T50FR-TLY | Flame Retardant Polyethylene | Natural | 250 | 76.2 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -4°F – 122°F (-20°C – 50°C) | 0.060 | 1.52 | 1 |
| T62FR-CY | Flame Retardant Polyethylene | Natural | 100 | 30.5 | 1/2 – 4 1/2 | 12.7 – 114.3 | 0.62 | 15.9 | -4°F – 122°F (-20°C – 50°C) | 0.062 | 1.57 | 1 |
| T62FR-C20Y | Flame Retardant Polyethylene | Black | 100 | 30.5 | 1/2 – 4 1/2 | 12.7 – 114.3 | 0.62 | 15.9 | -4°F – 122°F (-20°C – 50°C) | 0.062 | 1.57 | 1 |
| T75FR-CY | Flame Retardant Polyethylene | Natural | 100 | 30.5 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -4°F – 122°F (-20°C – 50°C) | 0.065 | 1.65 | 1 |
| T75FR-C20Y | Flame Retardant Polyethylene | Black | 100 | 30.5 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -4°F – 122°F (-20°C – 50°C) | 0.065 | 1.65 | 1 |
| T75FR-TY | Flame Retardant Polyethylene | Natural | 200 | 61.0 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -4°F – 122°F (-20°C – 50°C) | 0.065 | 1.65 | 1 |
| T100FR-CY | Flame Retardant Polyethylene | Natural | 100 | 30.5 | 7/8 – 6 | 22.2 – 152.4 | 1.00 | 25.4 | -4°F – 122°F (-20°C – 50°C) | 0.070 | 1.78 | 1 |
| T100FR-C20Y | Flame Retardant Polyethylene | Black | 100 | 30.5 | 7/8 – 6 | 22.2 – 152.4 | 1.00 | 25.4 | -4°F – 122°F (-20°C – 50°C) | 0.070 | 1.78 | 1 |
| T12N-C | Nylon 6.6 | Natural | 100 | 30.5 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -40°F – 149°F (-40°C – 65°C) | 0.015 | 0.38 | 1 |
| T12N-D | Nylon 6.6 | Natural | 500 | 152.4 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -40°F – 149°F (-40°C – 65°C) | 0.015 | 0.38 | 1 |
| T19N-C | Nylon 6.6 | Natural | 100 | 30.5 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -40°F – 149°F (-40°C – 65°C) | 0.020 | 0.51 | 1 |
| T19N-M | Nylon 6.6 | Natural | 1,000 | 304.8 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -40°F – 149°F (-40°C – 65°C) | 0.020 | 0.51 | 1 |
| T25N-C | Nylon 6.6 | Natural | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 149°F (-40°C – 65°C) | 0.023 | 0.58 | 1 |
| T25N-M | Nylon 6.6 | Natural | 1,000 | 304.8 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 149°F (-40°C – 65°C) | 0.023 | 0.58 | 1 |
| T38N-C | Nylon 6.6 | Natural | 100 | 30.5 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 149°F (-40°C – 65°C) | 0.030 | 0.76 | 1 |
| T38N-TL | Nylon 6.6 | Natural | 250 | 76.2 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 149°F (-40°C – 65°C) | 0.030 | 0.76 | 1 |

*Flame retardant products are manufactured from a material that is rated UL 94V-0.
 ‡Reel packaging may contain splices. Contact Panduit Customer Service for further information.
 ^TFE is Polytetrafluorethylene material.

Continues on next page

Spiral Wrap (continued)

| Part Number | Material* | Color | Length Per Reel | | Bundle Diameter Range | | Outside Diameter | | Temperature Range | Wall Thickness | | Std. Pkg. Qty.‡ |
|-------------|--|---------|-----------------|-------|-----------------------|--------------|------------------|------|---------------------------------|----------------|------|-----------------|
| | | | Ft. | m | In. | mm | In. | mm | | In. | mm | |
| T50N-C | Nylon 6.6 | Natural | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 149°F (-40°C – 65°C) | 0.032 | 0.81 | 1 |
| T50N-TL | Nylon 6.6 | Natural | 250 | 76.2 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 149°F (-40°C – 65°C) | 0.032 | 0.81 | 1 |
| T62N-C | Nylon 6.6 | Natural | 100 | 30.5 | 1/2 – 4 1/2 | 12.7 – 114.3 | 0.62 | 15.9 | -40°F – 149°F (-40°C – 65°C) | 0.035 | 0.89 | 1 |
| T75N-C | Nylon 6.6 | Natural | 100 | 30.5 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -40°F – 149°F (-40°C – 65°C) | 0.040 | 1.02 | 1 |
| T75N-T | Nylon 6.6 | Natural | 200 | 61 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -40°F – 149°F (-40°C – 65°C) | 0.040 | 1.02 | 1 |
| T100N-C | Nylon 6.6 | Natural | 100 | 30.5 | 7/8 – 6 | 22.2 – 152.4 | 1.00 | 25.4 | -40°F – 149°F (-40°C – 65°C) | 0.045 | 1.14 | 1 |
| T12N-C0 | Weather Resistant Nylon 6.6 | Black | 100 | 30.5 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -40°F – 149°F (-40°C – 65°C) | 0.015 | 0.38 | 1 |
| T19N-C0 | Weather Resistant Nylon 6.6 | Black | 100 | 30.5 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -40°F – 149°F (-40°C – 65°C) | 0.020 | 0.51 | 1 |
| T19N-M0 | Weather Resistant Nylon 6.6 | Black | 1,000 | 304.8 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -40°F – 149°F (-40°C – 65°C) | 0.020 | 0.51 | 1 |
| T25N-M0 | Weather Resistant Nylon 6.6 | Black | 1,000 | 304.8 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 149°F (-40°C – 65°C) | 0.023 | 0.58 | 1 |
| T25N-C0 | Weather Resistant Nylon 6.6 | Black | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.4 | 0.25 | 6.4 | -40°F – 149°F (-40°C – 65°C) | 0.023 | 0.58 | 1 |
| T38N-C0 | Weather Resistant Nylon 6.6 | Black | 100 | 30.5 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 149°F (-40°C – 65°C) | 0.030 | 0.76 | 1 |
| T50N-C0 | Weather Resistant Nylon 6.6 | Black | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 149°F (-40°C – 65°C) | 0.032 | 0.81 | 1 |
| T50N-TL0 | Weather Resistant Nylon 6.6 | Black | 250 | 76.2 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 149°F (-40°C – 65°C) | 0.032 | 0.81 | 1 |
| T62N-C0 | Weather Resistant Nylon 6.6 | Black | 100 | 30.5 | 1/2 – 4 1/2 | 12.7 – 114.3 | 0.62 | 15.9 | -40°F – 149°F (-40°C – 65°C) | 0.035 | 0.89 | 1 |
| T75N-C0 | Weather Resistant Nylon 6.6 | Black | 100 | 30.5 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -40°F – 149°F (-40°C – 65°C) | 0.040 | 1.02 | 1 |
| T100N-C0 | Weather Resistant Nylon 6.6 | Black | 100 | 30.5 | 7/8 – 6 | 22.2 – 152.4 | 1.00 | 25.4 | -40°F – 149°F (-40°C – 65°C) | 0.045 | 1.14 | 1 |
| T25NZFR-C20 | Low Smoke Halogen-Free Flame-Retardant Nylon | Black | 100 | 30.5 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -40°F – 149°F (-40°C – 65°C) | 0.023 | 0.58 | 1 |
| T38NZFR-C20 | Low Smoke Halogen-Free Flame-Retardant Nylon | Black | 100 | 30.5 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 149°F (-40°C – 65°C) | 0.030 | 0.76 | 1 |
| T50NZFR-C20 | Low Smoke Halogen-Free Flame-Retardant Nylon | Black | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 149°F (-40°C – 65°C) | 0.032 | 0.81 | 1 |

*Flame retardant products are manufactured from a material that is rated UL 94V-0.

‡Reel packaging may contain splices. Contact Panduit Customer Service for further information.

^TFE is Polytetrafluorethylene material.

Continues on next page

Spiral Wrap (continued)

| Part Number | Material* | Color | Length Per Reel | | Bundle Diameter Range | | Outside Diameter | | Temperature Range | Wall Thickness | | Std. Pkg. Qty.‡ |
|-------------|--|---------|-----------------|------|-----------------------|--------------|------------------|------|------------------------------------|----------------|------|-----------------|
| | | | Ft. | m | In. | mm | In. | mm | | In. | mm | |
| T75NZFR-C20 | Low Smoke Halogen-Free Flame-Retardant Nylon | Black | 100 | 30.5 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -40°F – 149°F (-40°C – 65°C) | 0.040 | 1.02 | 1 |
| T38P-C0 | Weather Resistant Polypropylene | Black | 100 | 30.5 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -40°F – 239°F (-40°C – 115°C) | 0.030 | 0.76 | 1 |
| T50P-C0 | Weather Resistant Polypropylene | Black | 100 | 30.5 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -40°F – 239°F (-40°C – 115°C) | 0.030 | 0.76 | 1 |
| T100P-C0 | Weather Resistant Polypropylene | Black | 100 | 30.5 | 7/8 – 6 | 22.2 – 152.4 | 1.00 | 25.4 | -40°F – 239°F (-40°C – 115°C) | 0.030 | 0.76 | 1 |
| T12T-C | TFE^ | Natural | 100 | 30.5 | 1/16 – 1/2 | 1.6 – 12.7 | 0.12 | 3.2 | -454°F – 356°F (-270°C – 180°C) | 0.020 | 0.51 | 1 |
| T19T-C | TFE^ | Natural | 100 | 30.5 | 1/8 – 1 | 3.2 – 25.4 | 0.19 | 4.8 | -454°F – 356°F (-270°C – 180°C) | 0.030 | 0.76 | 1 |
| T25T-L | TFE^ | Natural | 50 | 15.2 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -454°F – 356°F (-270°C – 180°C) | 0.030 | 0.76 | 1 |
| T25T-L0 | TFE^ | Black | 50 | 15.2 | 3/16 – 2 | 4.8 – 50.8 | 0.25 | 6.4 | -454°F – 356°F (-270°C – 180°C) | 0.030 | 0.76 | 1 |
| T38T-L | TFE^ | Natural | 50 | 15.2 | 5/16 – 3 | 7.9 – 76.2 | 0.38 | 9.5 | -454°F – 356°F (-270°C – 180°C) | 0.030 | 0.76 | 1 |
| T50T-Q | TFE^ | Natural | 25 | 7.6 | 3/8 – 4 | 9.5 – 101.6 | 0.50 | 12.7 | -454°F – 356°F (-270°C – 180°C) | 0.030 | 0.76 | 1 |
| T62T-Q | TFE^ | Natural | 25 | 7.6 | 1/2 – 4 1/2 | 12.7 – 114.3 | 0.62 | 15.9 | -454°F – 356°F (-270°C – 180°C) | 0.030 | 0.76 | 1 |
| T75T-X | TFE^ | Natural | 10 | 3.1 | 5/8 – 5 | 15.9 – 127.0 | 0.75 | 19.1 | -454°F – 356°F (-270°C – 180°C) | 0.030 | 0.76 | 1 |
| T100T-X | TFE^ | Natural | 10 | 3.1 | 7/8 – 6 | 22.2 – 152.4 | 1.00 | 25.4 | -454°F – 356°F (-270°C – 180°C) | 0.040 | 1.02 | 1 |

*Flame retardant products are manufactured from a material that is rated UL 94V-0.

‡Reel packaging may contain splices. Contact Panduit Customer Service for further information.

^TFE is Polytetrafluorethylene material.

B1.
Cable
TiesB2.
Cable
AccessoriesB3.
Stainless
Steel Cable
Ties &
AccessoriesC1.
Wiring
DuctC2.
Abrasion
ProtectionC3.
Cable
ManagementD1.
TerminalsD2.
Power
ConnectorsD3.
Grounding
ConnectorsE1.
Labeling
SystemsE2.
LabelsE3.
Pre-Printed
&
Write-On
MarkersE4.
Permanent
IdentificationE5.
Industrial
Safety
SolutionsF.
Keystone
Cabling
SystemsG.
Part
Number
Index