


ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





TCF15 15A 600V Finger Safe Class J Fuse Bussmann Fuses

Catalog Number	TCF15
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class CF Fuse, TCF, Time-Delay,
	Dual-Element Current Limiting Cube Fuse, 15 A, Indicating Fuse,
	Interrupting Rating Of 100 Ka At 300 VDC and 300 Ka At 600 Vac

Weight per unit 0.1000 (lbs/each) **Tools & Testers** Product Category

Features

100.00	
amperage rating	5
connection	Blade End
dimensions	1.8800 IN X 0.7500 IN X 1.0000 IN
element	Dual
Fuse Class	Class CF
interrupt rating	100 kAIC at 300 Vdc300 kAIC at 600 Vac
Material	Glass Filled PES
media	Yes
Response Time	10 S at 500%
Voltage Rating	600 Vac, 300 Vdc

Dimensions and Weight

|--|

Descriptions

Description	15A 600V FINGER SAFE CLASS J FUSE
extra long description	BUSS TCF15 TIME DELAY CUBEFUSE 15A
Features	The revolutionary BussmannTM series Low-PeakTM
	CUBEFuseTM delivers the smallest footprint compared to any
	Class CC, J or RK fuse solution — requiring up to 70 less space
	when combined with its unique fuse holder or UL 98 Listed
	Compact Circuit Protector switch. Freeing up space is powerful.
	And the CUBEFuse does just that, while packing up to a 300 kA
	interrupting rating and enabling higher equipment short-circuit
	current rating (SCCR). Available from 1 to 400 amps.
Long Description	Eaton Bussmann Series Class CF fuse, TCF, time-delay,
	dual-element current limiting cube fuse, 15 A, indicating fuse,
	interrupting rating of 100 kA at 300 Vdc and 300 kA at 600 Vac
Product Type	Time Delay Cubefuse 15A Ind
Special Features	Finger Safe



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

м	١.	_		4	c _	_ 1				c _					
ľ	۱,	12	n	111		CI		·Δr	' In	ГЛ	rr	ทว	ıTI	n	n
	v			u	а	L - I	u	C-1	'In	W		110		w	

Brand	Eaton
GTIN	00051712614993
Manufacturers Part Number	TCF15
UPC	051712614993

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Туре	FUSE
rkaging	

Packaging

Carton	12	
Weight Per each	0.1	

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security
	SystemsDatacenters - Facilities: Power DistributionCommercial /
	Institutional Buildings / Structures - Critical PowerInd Facilities &
	Factories - Facility: Power Distribution and ControlStationary
	Machinery and Equipment Outside Factory - HVAC
Mounting	35 mm DIN Rail, Chassis
standard	UL Listed ,CSA Certified,RoHS Compliant,CE Marked